

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 136500

PRIMARY CORNER DESCRIPTION M. C. So. bdy. Sec. 7

Alias 876860 Description M.C. left bank Umpqua River
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1579)

Set meander post, from which
An Ash 6" dia., bears N.75°E., 62 lks. dist.
An Ash 14" dia., bears S.35°W., 139 lks. dist.

GLO survey by Geo. F. Rigby, U.S. Cadastral Engineer, under Group #143, surveyed Oct/Nov. 1931 - (DCSO records Vol. 27 Page(s) 11650 and 11653)

(Page 11650)
Left bank of Umpqua River. No trace of the original meander corner.

(Page 11653)
Proportionate point,
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for meander cor. of fracl. secs. 7 and 18, with brass cap mkd:

T 22 S
M C / S 7
 S 18
 / R 8 W
 1931

from which
A Cottonwood 8" dia., bears N.17°15'E., 80 lks. dist. mkd.
T22S R8W S7 MC BT.
A Maple 20" dia., bears S.63°30'W., 151 lks. dist. mkd.
T22S R8W S18 MC BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Vernon "Ray" Tracy, crew - March 1963 - C.S. File 52/14-58

Found - Brass cap set in 1931, buried 28" below surface of ground.
30" Cottonwood tree, N.17¼°E., 52.8 ft. No scars visible. Tree alive and in good condition.
25" Maple S.63½°W., 99.7 ft. Scars dimly visible. Tree alive and in good condition.
Set 3/4" Rod on top of brass cap, extends approx. 4" above ground.
Reblaze and scribe:
25" Maple S.63½°W., 99.7 ft. mkd. "MC S18 CS BT"
New BT - Blaze and scribe 9" Maple N.60°W., 8.8 ft. mkd.
"M.C. S7 CS BT."