

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 31 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 376 survey dated Jan. 22, 1881 (DCSO records Vol. 4 Page(s) 1594)

-----  
Set post for ¼ sec. cor. from which  
A Fir 36" dia., bears S.35°E., 29 lks. dist.  
A Fir 30" dia., bears N.45°E., 10 lks. dist.

BLM resurvey by Harvey E. Wofford, Cadastral Surveyor, under Group #1005, surveyed July/Sept. 1980 - (DCSO records Vol. 43 Page(s) 16778-79)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:  
T 22 S R 8 W  
1/4 S 31  
T 23 S R 8 W  
1980

from which  
A Fir 12" dia., bears N.4°E., 77 lks. dist. mkd. ¼ S31 BT.  
A Fir 15" dia., bears N.58 3/4°E., 119½ lks. dist. mkd. X BT.

Cor. Fd. and used in BLM Sec. subdivision survey by Joel E. Robb, under Group #1166 - surveyed July/Aug. 1983 - (DCSO records, Vol. 46 Pages 17795)