TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 4 Page(s) 1609)

Set a Willow post for the ¼ sec. cor., from which
A Fir 48" dia., bears N.20°E., 78 lks. dist.
A Fir 32" dia., bears S.40°W., 100 lks. dist.

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #436, Surveyed April/May 1960 (DCSO records Vol. 30 Page(s) 12879)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼ S 30 / S 31
T 22 S R 8 W
1960

from which
A Fir 15" dia., bears N.86°E., 96 lks. dist. mkd. ¼ S30 BT
A Fir 8" dia., bears S.8°E., 121 lks. dist. mkd. ¼ S31 BT.

DCSO by MEG - 9/23/1963 (added 3/21/2018) C.S. File 52/14-19 - FD BC & both BT in good condition

---