TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 4 Page(s) 1611)

Set a Fir post, from which
A Hemlock 10" dia., bears N.47°E., 9 lks. dist.
A Hemlock 8" dia., bears S.45°W., 7 lks. dist.

BLM resurvey by Floyd Brooks and Peter Peterson, Cadastral Surveyors - under Group #'s 595 and 657 - surveyed Aug. 1965/Dec. 1967 - (DCSO records Vol. 34 Page(s) 14120)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼ S 19
S 30
T 22 S R 8 W
1965

from which
A Fir 19" dia., bears N.18°W., 37½ lks. mkd. ¼ S19 BT.
A Fir 12" dia., bears S.29½°W., 32½ lks. mkd. ¼ S30 BT.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2180 & 2300, surveyed May/Oct. 2007 (DCSO records Vol. 56 Page(s) 22220-1)

The ¼ sec. cor. of secs. 19 & 30, reestablished by Brooks and Peterson in 1965-67; monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd.
from which the remains of the BTs mkd. by Brooks and Peterson
A fir snag, 15" dia., bears S.29½°W., 20.4 ft., with a healed blaze. (Record, 21.5 ft.)
A roothole, bears N.18°W., 24.8 ft., alongside of which is a down fir stump, 24" dia., with a healed blaze.
and new bearing trees
A fir, 7" dia., bears N.58½°E., 3.1 ft., mkd. ¼ S19 BT.
A fir, 5" dia., bears S.9¼°E., 18.5 ft., mkd. ¼ S30 BT.
Corner is located in young timber on a very broad spur, slopes gently N., and W., 110 ft. from a graveled road, 15 ft. wide, extending N.10°E. and S.10°W., and E., 765 ft. from another graveled road, 12 ft. wide, extending N.50°E. and S.60°W.