

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 202 survey dated March 11, 1874 (DCSO records Vol. 4 Page(s) 1591)

Marked a Dogwood 8" dia. for the ¼ sec.cor., from which
A Fir 5" dia., bears N.20°W., 26 lks. dist.
A Fir 16" dia., bears S.30°E., 28 lks. dist.

GLO survey by Geo. F. Rigby, U.S. Cadastral Engineer, under Group #143, surveyed Oct/Nov. 1931 - (DCSO records Vol. 27 Page(s) 11650 and 11651)

(Page 11650)
No trace of the original ¼ sec. cor.
(Page 11651)
Proportionate point,
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap mkd: ¼ $\frac{S\ 18}{S\ 19}$
1931

from which
A Fir 40" dia., bears N.36°W., 26 lks. dist. mkd. ¼ S18 BT
A Fir 30" dia., bears S.3°30'W., 59 lks. dist. mkd. ¼ S19 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - M. Stone & V. Tracy, crew - August 1963 - C.S. File 52/14-60

Found - Govt. brass cap set in 1931, good condition.
40" D.Fir N.36°W., 17.2 ft., shows scar.
30" Fir S.3½°W., 38.9 ft. is uprooted and down, not recent, nearly buried. Did not hunt for scars.
New BTs -19" D.Fir N.52°W., 11.1 ft. mkd. ¼ S18 CS BT.
6" Hemlock S.29°E., 35.1 ft. mkd. ¼ S19 CS BT.

Cor. Fd. and used in BLM resurvey by Brooks and Peterson, Group #'s 595 and 657 - surveyed Aug. 1965/Dec. 1967 - (DCSO records, Vol. 34 Page 14123)