

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1579)

Set ¼ sec. post, from which
A Cottonwood, 48" dia., bears S.59°W., 755 lks. dist.
A W.Oak 18" dia., bears N.69°W., 268 lks. dist.

GLO survey by Geo. F. Rigby, U.S. Cadastral Engineer, under Group #143, surveyed Oct/Nov. 1931 - (DCSO records Vol. 27 Page(s) 11650 and 11653)

(Page 11650)
No trace of the original ¼ sec. cor. Set temp. stake.

(Page 11653)
Proportionate point,
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap mkd:
¼ $\frac{S 7}{S 18}$
1931

from which
A Maple 12" dia., bears N.4°W., 362 lks. dist. mkd. ¼ S7 BT.
An Oak 18" dia., bears S.52°15'E., 13.63 chs. dist. mkd. ¼ S18 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Vernon "Ray" Tracy, crew - March 1963 - C.S. File 52/14-57

Found - Brass cap at corner, top buried 24" below ground.
24" W.Oak S.52¼°E., 909.6 ft., shows very plain axe scar. Tree alive and in good condition.
12" W.Oak, not Maple, N.4°W., 238.9 ft. Tree dead, face rotted. Found fragment of reverse scribing on edge of overgrowth.

Set 3/4" Rod on top of Brass cap, rod extends approx. 6" above ground surface.

New Accessories:

A Power pole (Copco A2563 6-387 3) bears N.12°E., 9.3 ft. from ¼ corner.
21" W.Oak N.35°W., 216.7 ft. mkd. ¼ S7 CS BT. Tree stands at edge of high bank along river. (now stump)

Fd. OK, March 1980 by Les Roberts, M 83-74