

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 31 and 32 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 376 survey dated Jan. 22, 1881 (DCSO records Vol. 4 Page(s) 1593)

-----  
Set Maple post for sec. cor. to secs. 31 and 32, from which  
A Fir 50" dia., bears N.70°W., 21 lks. dist.  
A Fir 24" dia., bears N.8°E., 35 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Vernon Tracy, crew - Dec. 1962/Jan. 1963 - C.S. File 52/14-51

-----  
Found - 1¼" I.Pipe 15" above ground with cap stamped S31|S32  
S 6  
60" Fir N.70°W., 13.9 ft. (to face) with fairly plain bark scribing S31 T22S R8W.  
Rotten remains of Fir stump N.8°E., 23 ft., too far gone to find markings.  
New BT - 5" D.Fir N.38°E., 31.5 ft. mkd. S32 CS BT.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13674)

-----  
The cor. of secs. 31 and 32, monumented with an iron post not of record, 1½" dia., 10" above ground, firmly set, with brass cap marked: S 31|S 32  
S 6

from which the original bearing trees mkd. by Byars in 1881:  
A stump hole bears N.8°E., 35 lks. dist.  
A Fir 68" dia., bears N.70°W., 21 lks. dist. with scribe marks 2S R8W visible on bark blaze.  
and a bearing tree marked by the County Surveyor in 1963:  
A Fir 6" dia., bears N.38°E., 48 lks. dist. with scribe marks S32 CS BT visible on unhealed blaze.  
Add the marks BLM 1963 to brass cap.

BLM resurvey by Harvey Wofford, Cadastral Surveyor, under Group #1005, surveyed July/Sept. 1980 (DCSO records Vol. 43 Page(s) 16778)

-----  
The cor. of secs. 31 and 32 only, perpetuated and recorded by Godfrey in 1963, redescribed by Brooks and Jelley in 1963-65, monumented with an iron post 1½" dia. firmly set, projecting 16" above ground with iron cap mkd. BLM S31 S32 S6 1963.  
from which an original bearing tree:  
(Cont. Next Page)

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 31 and 32 only

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A Fir 63" dia., bears N.70°W., 25 lks. dist. with marks S3 R8W T visible on bark blaze. (Rec. and to face, 21 lks.)

and a bearing tree mkd. by Godfrey:

A Fir 8" dia., bears N.39°E., 48 lks. dist. with healed blaze. (Rec. N.38°E.)

From this point, the closing cor. of secs. 5 & 6, T23S R8W, bears S.89°37'E., 1.47 chs. dist.