

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 200120

PRIMARY CORNER DESCRIPTION S 1/16 Secs. 31 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Brooks and Jelley, under Group #'s 514 and 350 - surveyed June 1963/March 1965 - (DCSO records, Vol. 33 Pg 13701)

Point for the S 1/16 sec. cor. of secs. 31 and 32.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked

S 1/16
S 31|S 32
1963

from which
A fir, 5" dia., bears S.61½°E., 93½ lks., mkd. S 1/16 S32
BT.
A fir, 10" dia., bears N.27½°W., 39 lks., mkd. S1/16 S31
BT.

Rockne Luckman - For: International Paper Co. - June 1982 - M92-54

Found - Brass cap
8" D.Fir S.68°E., 2.4' - not of record
1963 BTs not found.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 7/29/2021 (Filed 11/8/2022) - C.S. File 67/54-58

Found - A 3¾" dia. Brass cap marked as described on 2" I.D. Iron Pipe projects 3" above ground.
A 24" dia., 1 ft. tall D.Fir stump with no remaining blaze evidence; bears S.27½°W., 25.7 ft. 1963
New - A 38" dia., D.Fir scribed "X" "BT" on high-low blazes, bears S.5°E., 43.9 ft.
A 37" dia., D.Fir showing healed high-low blazes (good scars but no record) bears S.81°W., 3.9 ft.
Note - Corner monument is at top of small cut bank on north edge of logging Rd. Area is relatively flat bench with old growth Fir, some new logging to NE.
Compass decl. 14¾°E.