TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 4 Page(s) 1608)

---

Set Fir post for ¼ sec. cor., from which
A Fir 8" dia., bears N.25°E., 15 lks. dist.
A Fir 12" dia., bears N.78°W., 26 lks. dist.

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #436, Surveyed April/May 1960 (DCSO records Vol. 30 Page(s) 12875-76)

---

The ¼ sec. cor., determined at record bearing and distance from the only remaining original bearing tree:
A Fir 30" dia., bears N.25°E., 15 lks. dist. with opened and rotted blaze. I open further and uncover illegible fragments of scribe marks.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼
S 31 | S 32
T 22 S R 8 W
1960

from which new bearing trees:
A Fir 13" dia., bears N.34°E., 31 lks. mkd. ¼ S32 BT.
A Fir 16" dia., bears S.44°W., 57 lks. dist. mkd. ¼ S31 BT

Fd. and used in BLM resurvey by Brooks and Jelley, under Group #'s 514 and 350 - surveyed June 1963/March 1965 - (DCSO records, Vol. 33 Page 13701)

Fd. and used in sec. subd. BLM survey by Joel E. Robb, under Group #1166 - surveyed July/Aug. 1983 - (DCSO records, Vol. 46 Pages 17796-97)

Fd. OK, June 10, 1982 by R.R. Luckman - M 92-54

David Edwards - Crew: Brant Miller & Eric Sprinkle - 5/16/2019 - C.S. File 65/102-52

---

Found - 1960 BLM Brans cap.
A 30" dia. Fir stump bears N.25°E., 8.9' original
A 22" dia. Fir stump bears N.36°E., 19.7' BLM 1960
The Fir S.44°W., is a windfall. BLM 1960
New - An 11" dia. Fir scribed "¼ S32 BT" bears S.44°E., 8.7'
Continued next page
A 14" dia. Fir scribed "¼ S31 BT" bears S.28°W., 15.4'
Set a 6 ft steel post 2' S.1°W.
Compass decl. 15°E. _____