

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 4 Page(s) 1608)

-
- Set Hemlock post for cor. to secs. 29, 30, 31 & 32 from which
- A Fir 30" dia., bears N.40°E., 91 lks. dist.
 - A Fir 15" dia., bears S.10°E., 50 lks. dist.
 - A Hemlock 7" dia., bears S.18°W., 14 lks. dist.
 - A Fir 24" dia., bears N.28°W., 44 lks. dist.

BLM resurvey by Floyd A Brooks, Cadastral Surveyor, under Group #436, Surveyed April/May 1960 (DCSO records Vol. 30 Page 12876)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd:

T22S R8W
S 30 | S 29
S 31 | S 32
1960

from which

- A D.Fir 30" dia., bears N.15½°E., 40 lks. dist. mkd. T22S R8W S29 BT.
- A W.Fir 8" dia., bears S.19½°E., 18 lks. dist. mkd. T22S R8W S32 BT.
- A W.Fir 5" dia., bears S.80½°W., 67 lks. dist. mkd. T22S R8W S31 BT.
- A D.Fir 5" dia., bears N.68°W., 67 lks. dist. mkd. T22S R8W S30 BT.

Fd. OK, June 10, 1982 by R.R. Luckman - M 92-54

BLM remonumentation by Aaron M Graham, Cadastral Surveyor & Michael O Jones Surveying Tech, under Group No 2241, surveyed Nov. 2008/April 2009 - (DCSO records Vol. 56 Page(s) 22115)

The cor. of secs. 29, 30, 31, and 32, reestablished by Brooks in 1960; monumented with an iron post, 2½" dia., firmly set, projecting 2" above ground, with a brass cap (properly) mkd. from which the remains of the bearing trees mkd. by Brooks

- A fir, 38" dia., bears N.18°E., 26.4 ft., with a healed blaze. (Record, N.15½°E.)
 - A fir, 20" dia., bears S.19½°E., 11.9 ft., with a healed blaze.
 - A fir, 24" dia., bears S.82°W., 44.2 ft., with a healed blaze. (Record, S.80½°W.)
 - A fir snag, 12" dia., bears N.67°W., 44.2 ft., no marks visible (Record, N.68°W.)
- continued next page

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and a new bearing tree

A fir, 15" dia., bears N.23°W., 6.7 ft., mkd. T22S R8W S30
BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail)
driven at the base right side-center.