

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 4 Page(s) 1610)

Set a Fir post for the cor. to secs. 19, 20, 29 and 30, from which

- A Hemlock 8" dia., bears N.43°E., 32 lks. dist.
- A Fir 36" dia., bears S.55°E., 50 lks. dist.
- A Fir 36" dia., bears S.57°W., 77 lks. dist.
- A Hemlock 8" dia., bears N.1°W., 40 lks. dist.

BLM resurvey by Floyd Brooks and Peter Peterson, Cadastral Surveyors - under Group #'s 595 and 657 - surveyed Aug. 1965/Dec. 1967 - (DCSO records Vol. 34 Page(s) 14118)

The sec. cor., at proportionate distance latitudinally and at record distance in departure from the cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22 S R 8 W
S 19 | S 20
S 30 | S 29
1965

from which

- A Fir 12" dia., bears N.37°E., 23 lks. dist. mkd. T22S R8W S20 BT.
- A Fir 8" dia., bears S.34°E., 14 lks. dist. mkd. T22S R8W S29 BT.
- A Fir 10" dia., bears S.83°W., 28 lks. dist. mkd. T22S R8W S30 BT.
- A Fir 8" dia., bears N.63½°W., 25½ lks. dist. mkd. T22S R8W S19 BT.

Mark Smalley - for: Roseburg Forests Products - Oct. 7, 1997 - C.S. 65/15-16

Mon. Fd.- 1965 Cadastral I.P.B.C.
Bt's Fd.- 12" Fir Stump, N.38°E., 15.9'.
8" Fir Stump, S.34°E., 9.2', visible scribe
8" Fir Stump, S.86°W., 17.3'.

New Accessories -
2 - 5/8" x 48" I.R. with tags North 10' & West 10'.

6' steel fence post set near corner.

Sec. cor falls in a clear cut - no trees available - pt tags on remaining BT stumps.

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias	Description

BLM remonumentation by Aaron M Graham, Cadastral Surveyor & Michael O Jones Surveying Tech, under Group No 2241, surveyed Nov. 2008/April 2009 - (DCSO records Vol. 56 Page(s) 22116-7)

The cor. of secs. 19, 20, 29, and 30, reestablished by Brooks and Peterson in 1965-67; monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd.

from which the remains of the BTs mkd. by Brooks and Peterson
A decayed fir stump, 17" dia., bears N.37°E., 15.2 ft., no marks visible.

A decayed fir stump, 10" dia., bears S.39°E., 9.2 ft., no marks visible. (Record, S.34°E.)

A decayed fir stump, 12" dia., bears S.83°W., 17.3 ft., no marks visible. (Record, 18.5 ft.)

and the reference monuments set by Smalley, in 1997

An iron rod, 5/8" dia., firmly set, projecting 18" above ground, bears North, 10.0 ft. Set an aluminum cap, 2¼" dia., mkd. RM T22S R8W 10.0 FT TO COR S20 2009, on top of the iron rod.

An iron rod, 5/8" dia., firmly set, projecting 18" above ground, bears S.82°W., 9.8 ft. Set an aluminum cap, 2¼" dia., mkd. RM T22S R8W 9.8 FT TO COR S30 2009, on top of the iron rod.

and new bearing trees

A fir, 6" dia., bears N.41°E., 13.5 ft., mkd. X BT.

A fir, 6" dia., bears S.56°E., 24.3 ft., mkd. X BT.

A fir, 7" dia. bears S.12°W. 32.3 ft. mkd. T22S R8W S30 BT

A fir, 8" dia. bears N.53°W. 12.8 ft. mkd. T22S R8W S19 BT

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

The geographic position (NAD 1983 (CORS 96)) of the corner of sections 19, 20, 29, & 30, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's OPUS, is as follows:

Latitude: 43°38'06.75"N. Longitude: 123°41'01.98"W.