

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 4 Page(s) 1611)

Marked Chittem wood, 5" dia., for ¼ sec.cor., from which
A Fir 8" dia., bears N.45°E., 20 lks. dist.
A Fir 13" dia., bears N.30°W., 30 lks. dist.

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #436, Surveyed April/May 1960 (DCSO records Vol. 30 Page(s) 12876)

The ¼ sec. cor., determined at record bearing and distance from the only remaining original bearing tree:

A W.Fir 22" dia., bears N.45°E., 20 lks. dist. with a healed blaze. I open and uncover scribe mark S.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

¼
S 19 | S 20
T 22 S R 8 W
1960

from which new bearing trees

A W.Fir 10" dia., bears S.16°E., 96 lks. dist. mkd. ¼ S20 BT.

A D.Fir 20" dia., bears N.46½°W., 24 lks. dist. mkd. ¼ S19 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Vernon "Ray" Tracy, crew - March 1963 - C.S. File 52/14-55

Found - GLO brass cap set in 1963.

W.Fir snag N.45°E., 13.2 ft., scribing visible "S".
Orig. BT.

13" W.Fir S.16°E., 63.4 ft., scribing visible in not completely healed blaze. Tree alive and in good condition.

Fir snag, recently broken off, N.46½°W., 15.8 ft.
scribe visible in not completely healed blaze.

New BT - 18" W.Fir S.59°W., 24.9 ft. mkd. ¼ S19 CS BT.

Corner lies approx. 200 ft. South of ridge top.

Fd. and used in BLM resurvey by Brooks and Peterson, under Group #'s 595 and 657, surveyed Aug. 1965/Dec. 1967 - (DCSO records, Vol. 34 Page 14121)

continued next page

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2180 & 2300, surveyed May/Oct. 2007 (DCSO records Vol. 56 Page(s) 22222-3)

The ¼ sec. cor. of secs. 19 and 20, perpetuated by Brooks in 1960; monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd. from which the remains of an original bearing tree

A pile of fir duff, 2 ft. across, bears N.45°E., 13.2 ft., no marks visible.

and the remains of the bearing trees mkd. by Brooks

A W.Fir stump, 36" dia., bears S.16°E., 63.4 ft., with a healed blaze.

A fir snag, 12" dia., bears N.44°W., 15.8 ft., no marks visible. (Record, N.46½°W.)

and a bearing tree mkd. by Godfrey in 1962-63 and reported by Brooks and Peterson in 1965-67 as being mkd. by the Douglas County Surveyor in 1963

A W.Fir, 36" dia., bears S.60°W., 24.8 ft., with a healed blaze.

and a new bearing tree

A W.Fir, 19" dia., bears S.43¾°E., 5.7 ft., mkd. ¼ S20 BT. Corner is located on a SW. slope on the E. edge of timber, bears N. and S., with newly logged area to the E.