

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1579)

- 
- Set post cor. to secs. 7, 8, 17 and 18, from which
- A Fir 4" dia., bears S.9°E., 7 lks. dist.
  - A Fir 6" dia., bears S.28°W., 33 lks. dist.
  - A Fir 6" dia., bears N.56°W., 43 lks. dist.
  - A Live Oak 14" dia., bears N.70°E., 29 lks. dist.

GLO survey by Geo. F. Rigby, U.S. Cad. Engineer, under Group #143, surveyed Oct/Nov. 1931 - (DCSO rec Vol. 27 Pg 11652)

-----

Point of the original cor., determined from three of the old bearing trees. At this point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground,, with brass cap mkd:

T 22	S R 8 W
S 7	S 8
S 18	S 17
1931	

- from which
- Old bearing trees:
- A Fir 30" dia., bears S.9°E., 7 lks. dist. mkd. with a scar of an old blaze but no scribe marks.
  - A Fir 14" dia., bears S.28°W., 33 lks. dist. mkd. T22S R8W S18 BT, under 4" of overgrowth.
  - A Fir 15" dia., bears N.56°W., 43 lks. dist. mkd. with a scar of an old blaze but no scribe marks.
- New bearing trees:
- A Fir 5" dia., bears N.83°E., 33 lks. mkd. T22S R8W S8 BT.
  - A Fir 60" dia., bears S.19°E., 76 lks. mkd T22S R8W S17 BT
  - A Fir 12" dia. bears S.8°15'W. 23 lks mkd. T22S R8W S18 BT
  - A Fir 26" dia. bears N.81°45'W. 33 lks mkd. T22S R8W S7 BT

Fd. & used in BLM resurvey by Brooks & Jelley, Group # 514 & 350, surveyed 6/1963-3/1965 (DCSO rec, Vol. 33 Pg 13704)

Fd. OK, March 1980, Les Roberts, M 83-34

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2180 & 2300, surveyed May/Oct. 2007 (DCSO records Vol. 56 Page(s) 22228-9)

-----

The cor. of secs. 7, 8, 17, & 18, perpetuated by Rigby in 1931, and recovered by Brooks and Jelley in 1963-65; monumented with a rusted iron pipe, 2" dia., firmly set, with concrete core projecting 3" above ground, in a mound of stone, 3 ft. base, to top, from which the original BTs

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A fir, 49" dia., bears S.9°E., 4.6 ft., with axe marks and a healed blaze.

A fir, 33" dia., bears N.53<sup>3</sup>/<sub>4</sub>°W., 28.4 ft., with a healed blaze. (Record, N.56°W.)

and the bearing trees mkd. by Rigby

A fir, 27" dia., bears N.86<sup>1</sup>/<sub>4</sub>°E., 21.8 ft., with a healed blaze. (Record, N.83°E.)

A fir, 72" dia., bears S.19°E., 50.2 ft., with a healed blaze. Tree is behind the original SE. bearing tree.

A fir, 21" dia., bears S.8<sup>1</sup>/<sub>4</sub>°W., 15.2 ft., with a healed blaze. Tree is partially behind the original SE. bearing tree.

A fir, 46" dia., bears N.81<sup>3</sup>/<sub>4</sub>°W., 21.8 ft., no marks visible.

At the corner point

Set a stainless steel post, 28" long, 2<sup>1</sup>/<sub>2</sub>" dia., 22" in the ground, directly over the rusted iron pipe and concrete core, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 22 S R 8 W  
S 7 | S 8  
S 18 | S 17  
2007

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located on a W. slope in young timber, near the northerly point of a stand of large timber, and W., 375 ft. of a dirt road, 6 ft. wide, extending N.5°W. and S.60°E.