

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias <u>876820</u>	Description <u>M.C. left bank Umpqua River</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1578)

-----  
Set meander and  $\frac{1}{4}$  sec. post, from which  
A Maple 15" dia., bears S.70°E., 43 lks. dist.  
A Maple 5" dia., bears N.48°W., 24 lks. dist.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13705)

-----  
Point for the  $\frac{1}{4}$  sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:  
 $\frac{1}{4}$   
S 7 S 8  
T 22 S R 8 W  
1963

from which  
A Fir 16" dia., bears S.71 $\frac{1}{2}$ °E., 46 lks. dist. mkd.  $\frac{1}{4}$  S8 BT  
An Alder 15" dia., bears S.27°W., 19 lks. dist. mkd.  $\frac{1}{4}$  S7 BT.