

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars Deputy Surveyor under contract # 202 survey dated March 11, 1874 (DCSO records Vol 4 Page 1590)  
-----  
Set a granite stone, 20 x 10 x 4 for cor. to secs. 5, 6, 7 and 8. No trees.  
A. Sawyer's house bears N.77°E.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13706)  
-----  
Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:  
T 22 S R 8 W  
S 6 | S 5  
S 7 | S 8  
1963  
from which  
A Maple 8" dia., bears N.18½°E., 81 lks. dist. mkd. T22S R8W S5 BT.  
A Maple 15" dia., bears S.5°E., 44 lks. dist. mkd. T22S R8W S8 BT.  
A Maple 20" dia., bears S.72°W., 100 lks. dist. mkd. T22S R8W S7 BT.  
A rock outcrop 6 ft. high, bears N.32°W., 32 lks. dist. mkd. X B O on lower portion.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor and Michael O. Jones Surveying Technician, under Group #2199, surveyed April 2008/April 2009 - (DCSO rec Vol 56 Page 21944)  
-----  
The cor. of secs. 5, 6, 7, and 8, reestablished by Brooks and Jelley in 1963-65; monumented with an iron post, 2½" dia., firmly set, with top flush with the surface of the ground, with a brass cap (properly) mkd.  
from which the bearing trees and a bearing object mkd. by Brooks and Jelley in 1963-65  
A maple, 15" dia., bears N.18½°E., 53.5 ft., with a healed blaze.  
A maple, 24" dia., bears S.5°E., 27.3 ft., no marks visible. (Record, 29.0 ft.)  
A maple, 33" dia bears S.72°W. 66.0 ft with a healed blaze  
A rock outcrop, 6 ft. high, bears N.32°W., 21.1 ft., mkd. X BO on the lower portion.  
An iron pipe, 1 in. diam., projecting 18 ins., established by person(s) unknown for unknown purpose is alongside the cor.