

PRIMARY CORNER DESCRIPTION So. Sec. cor. 31 & 32 only, T21-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 2 Page(s) 872)

-----  
Set a post 6" dia., 4 ft. long on mound of stone 18" high, 3 ft. sq. at base for cor. to secs. 31 and 32, mkd. T21S S32 on NE./ T22S R8W S5 on SE.; S6 on SW.; S31 on NW. face with one notch on W. and 5 on E. edge.  
No witness trees.

GLO survey by Norman D. Price, Cadastral Engineer and Geo. Rigby, Assoc. Cadastral Engineer, under Group #282, surveyed May/Aug. 1945 (DCSO records Vol. 27 Page(s) 11375)

-----  
Proportional measurement.  
Set an iron post 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 31 and 32, with brass cap mkd. T 21 S R 8 W  
S 31 S 32  
T 22 S R 8 W  
S 5  
1945

from which  
A dead Fir 18" dia., bears N.9°E., 51 lks. dist. mkd. T21S R8W S32 BT.  
A dead Fir 40" dia., bears N.19½°W., 182 lks. dist. mkd. T21S R8W S31 BT.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13679)

-----  
The cor. of secs. 31 and 32, monumented with an iron post 2" dia., 10" above ground, firmly set, with 1945 brass cap. from which the remaining bearing tree mkd. by Price,  
A sawed Fir stump 38" dia., bears N.19½°W., 182 lks. dist. with fragmentary scribe marks visible on burned face of blaze.  
and new bearing trees:  
A sawed Fir stump 40" dia., bears N.9°E., 186 lks. dist. mkd. T21S R8W S32 BT.  
A sawed Fir stump 50" dia., bears N.71°W., 102 lks. dist. mkd. T21S R8W S31 BT.  
Set a 7 ft. steel fence post, 2 ft. in the ground alongside the iron post.