

PRIMARY CORNER DESCRIPTION Center 1/4 Corner for Section 32

| Alias | Description |
|-------|-------------|
| | |
| | |
| | |
| | |

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13724)

Point for the center ¼ sec.cor. of sec. 32, at intersection with the E. and W. center line.
Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap marked: C ¼ S 32
1964

from which

A Hemlock 19" dia., bears S.38°E., 99 lks. dist. mkd. C ¼ S32 BT.

A Fir 17" dia., bears N.24½°W., 99 lks. dist. mkd. C ¼ S32 BT.

Survey by Rockne R. Luckman, LS #1254 - For: International Paper Co. - June 10, 1982 - M 92-54

Found - Brass cap. Govt. resurvey.
19" Hemlock, now a stump with tags, bears S.38°E., 66.0 ft.
17" Fir, now snag with blazes, bears N.24½°W., 66.0 ft.

New BT - 3 ft. Fir bears N.22°W., 9.8 ft. (not of record)

BLM remonumentation by Aaron M Graham, Cadastral Surveyor & Michael O Jones Surveying Tech, under Group No 2241, surveyed Nov. 2008/April 2009 - (DCSO records Vol. 56 Page(s) 22121)

The center ¼ sec. cor. of sec. 32, established by Brooks and Jelley in 1963-65; monumented with an iron post, 2½" dia., firmly set, projecting 8" above ground, with a brass cap (properly) mkd.

from which new bearing trees

A fir, 12" dia., bears N.7°E., 4.7 ft., mkd. C¼ S32 BT.

A fir, 8" dia., bears N.87°E., 10.0 ft., mkd. C¼ S32 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

The geographic position (NAD 1983 (CORS 96)) of the center ¼ section corner of section 32, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's OPUS, is as follows:

Latitude: 43°36'50.34"N Longitude: 123°40'27.71"W