

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 4 Page(s) 1609)

Set Fir post for ¼ sec. cor., from which
A Fir 50" dia., bears N.35°E., 61 lks. dist.
A Fir 60" dia., bears South, 24 lks. dist.

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #436, Surveyed April/May 1960 (DCSO records Vol. 30 Page(s) 12878)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:
¼ $\frac{S\ 29}{S\ 32}$
T 22 S R 8 W
1960

from which
A Chinquapin 5" dia., bears N.64°W., 88 lks. dist. mkd. ¼ S29 BT.
A Fir 16" dia., bears S.60°W., 223 lks. dist. mkd. ¼ S32 BT.

Fd. and used in BLM sec. subd. survey by Brooks and Peterson, under Group #'s 595 and 657, surveyed Aug. 1965/Dec. 1967 - (DCSO records, Vol. 34 Page 14129)

Survey by Rockne R. Luckman, LS #1254 - For: International Paper Co. - June 10, 1982 - M 92-54

Found - Brass cap.
27" D.Fir (rec. 16") bears S.60°W., 148.75 ft. Cut face and tag.
12" Chinquapin (Rec. 5") bears N.64°W., 58± ft. (no blaze or tag, but ribbon is sticking out of bark)
New BT - 9" D.Fir bears N.56°W., 15.0 ft. (not of record)

BLM remonumentation by Aaron M Graham, Cadastral Surveyor & Michael O Jones Surveying Tech, under Group No 2241, surveyed Nov. 2008/April 2009 - (DCSO records Vol. 56 Page(s) 22114)

The ¼ sec. cor. of secs. 29 and 32, reestablished by Brooks in 1960; monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd. from which a bearing tree mkd. by Brooks
A chinquapin, 17" dia., bears N.64°W., 58.1 ft., no marks visible.
continued next page

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 32

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

and new bearing trees

A fir, 20" dia., bears S.36°W., 9.9 ft., mkd. ¼ S32 BT.

A fir, 26" dia., bears N.74°W., 15.9 ft., mkd. ¼ S29 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.