

PRIMARY CORNER DESCRIPTION CC intersection S. bdy DLC #45

Alias	Description

BLM resurvey by Floyd Brooks and Peter Peterson, Cadastral Surveyors - under Group #'s 595 and 657 - surveyed Aug. 1965/Dec. 1967 - (DCSO records Vol. 34 Page(s) 14130)

Point for the closing cor, at intersection with the S. bdy. of Claim No. 45.

Set an iron post, 28" long, 2" dia., 24" in the ground, with brass cap mkd:

C 45
C
CC|S 29
C
T22S R8W
1965

from which

A fir, 6" dia., bears S.56°E., 111½ lks., mkd. T22S R8W S29 CC BT.

A fir, 9" dia., bears S.26°W., 73 lks., mkd. T22S R8W S29 CC BT.

From this point the SW. cor. of Claim No. 45, bears S.89°33'W., 16.06 chs.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 9/26/2005 - C.S. File 67/13-12

Found - 3" brass cap on 2½" iron post, (properly marked) projects 8" above ground.

Orig. 9" now 21" D.Fir, fully healed single blaze visible bears S.26°W., 48.2 ft. (agrees w/rec.) 1965 BT.

Orig. 6" now 13" D.fir, fully healed single blaze visible bears S.56°E., 73.6 ft. (agrees w/rec.) 1965 BT

New - ¾" I.D. iron pipe, projects 15" above ground, firmly set bears S.1°W., 2.75 ft.

14" dia., D.Fir double blazed & scribed "CC DLC 45 CS BT" bears N.79°W., 20.7 ft.

3" BC on 2½ iron post marking center South 1/16 corner bears S.1°57'E., 83.82 ft.

Note - Corner lies 2 ft. north of east-west fence-line. Compass decl. 16¾°E.

BLM remonumentation by Aaron M Graham, Cadastral Surveyor & Michael O Jones Surveying Tech, under Group No 2241, surveyed Nov. 2008/April 2009 - (DCSO records Vol. 56 Page(s) 22118-9)

The closing cor. at intersection with the N & S center line of sec. 29, established by Brooks & Peterson in 1965-67; monumented with an iron post, 2½" dia., cont. next pg

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 240221

PRIMARY CORNER DESCRIPTION CC intersection S. bdy DLC #45

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

firmly set, projecting 10" above ground, with a brass cap (properly) mkd.
from which the bearing trees mkd. by Brooks and Peterson
 A fir, 14" dia., bears S.56°E., 73.6 ft., with a healed blaze.
 A fir, 22" dia., bears S.26°W., 48.2 ft., no marks visible.
and a bearing tree mkd. by Smith, in 2005
 A fir, 14" dia., bears N.78°W., 21.0 ft., with scribe marks CC DLC 45 CS BT visible on partially healed blaze
A galvanized iron pipe, 1" dia. firmly set, projecting 16" above ground, bears S.1°W., 2.75 ft. of the iron post.
Corner is located 2 ft. N. of an E. and W. fence.