

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1577-78)

Set ¼ sec. post, from which
 A W.Oak 24" dia., bears S.12°W., 349 lks. dist.
 A W.Oak 30" dia., bears N.85°W., 636 lks. dist.
Andrew Sawyer's house bears S.20°W., 277 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - M. Stone & V. Tracy, crew - Sept. 1963 - C.S. File 52/14-61

Found - 62" W.Oak N.85°W., 419.8 ft., opened and found straight portion of scribe mark, also reverse on overgrowth. Center portion of face had rotted away before healing over.

No trace of SW BT.

Set Brass cap at cor. mkd: County Surveyors Office

T 22 S R 8 W

¼ $\frac{S}{S}$
 5
 8

1963

Cap buried 12" below surface in field.

Found - 28" W.Oak scribed "¼ S8 BT" by cadastral survey, 1963, bears S.28½°E., 225.7 ft. I add scribing "CS".

New BT - 14" W.Oak S.14½°W., 359.3 ft. mkd. ¼ S8 CS BT.

No suitable trees near to North of line.

(Brass cap set by Cadastral Survey, 1963, top buried 24" below ground surface, bears S.59°E., 89.7 ft.)

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13707)

The ¼ sec. cor., perpetuated and recorded by the County in 1963, monumented with an iron post, 28" long, 1" dia., firmly set, with top 22" below surface of ground, with 1963 B.C. from which the remaining original bearing tree

 A W.Oak 60" dia., bears N.85°W., 636 lks. dist., with fragmentary scribe marks visible on opened blaze.
and bearing trees mkd. by the County

 A W.Oak 29" dia., bears S.28°E., 342½ lks. dist. with scribe marks CS ¼ S8 BT visible on unhealed blaze.

 A W.Oak 15" dia., bears S.14½°W., 545 lks. dist., with scribe marks CS ¼ S8 BT visible on unhealed blaze.

ADD the marks B L M to brass cap.

Corner falls in field, at top of ascent, slopes S.

CONT.

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. BC 1.5 ft. below surface in pasture, good condition by M
Calvert ODOT - 3/2011 - ST. HWY 0=38-019A