

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 4 Page(s) 1605)

-----  
Set a Fir post for the ¼ sec. cor., from which  
A Fir 18" dia., bears N.62°E., 37 lks. dist.  
A Maple 8" dia., bears S.30°E., 8 lks. dist.

BLM resurvey by Floyd Brooks, Cadastral Surveyor - under Group #436 - surveyed May/June 1962 - (DCSO records Vol. 31 Page(s) 13110-11)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼  
S 32 S 33  
T 22 S R 8 W  
1962

from which

A Fir 40" dia., bears S.49½°E., 44 lks. dist. mkd. ¼ S33  
BT.

A Fir 50" dia., bears N.36°W., 57 lks. dist. mkd. ¼ S32  
BT.