

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. cor. for 28, 29, 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 4 Page(s) 1605)

Set a Laurel post for the cor. to secs. 28, 29, 32 and 33, from which

- A Fir 6" dia., bears N.1°E., 167 lks. dist.
- A Laurel 6" dia., bears S.62°E., 55 lks. dist.
- A Laurel 10" dia., bears S.58°W., 82 lks. dist.
- A Fir 24" dia., bears N.42°W., 66 lks. dist.

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #436, Surveyed April/May 1960 (DCSO records Vol. 30 Page(s) 12877)

The Sec. Cor., determined from the remaining original bearing trees:

- A Madrone 18" dia., bears S.61°E., 50 lks. dist. (slope dist., 55 lks.) with fragmentary scribe marks visible on bark. (Rec. brg. & dist., S.62°E., 55 lks.)
- A Madrone 24" dia., bears S.52°W., 78 lks. dist. (slope dist. 82 lks.) with no marks remaining. (Rec. brg. & dist., S.58°W., 82 lks.)
- A Fir turn out, 50" dia., the stump hole of which bears N.64°W., 60 lks. dist. (slope dist., 66 lks.) with no marks remaining. (Rec. brg. & dist., N.42°W., 66 lks.)

There is no remaining evidence of the NE. BT.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T	22	S	R	8	W
	S	29		S	28
	S	32		S	33
				1960	

from which new bearing trees

- A D.Fir 9" dia., bears S.35°W., 102 lks. dist. mkd. T22S R8W S32 BT.
- A W.Fir 6" dia., bears N.38°W., 45 lks. dist. mkd. T22S R8W S29 BT.

No suitable bearing tree available to the NE.

Fd. and used in BLM survey by Brooks, Group #436, surveyed May/June 1962 - (DCSO records, Vol. 31 Page 13111) AND by Brooks and Peterson, Group #'s 595 and 657, surveyed Aug 1965/Dec. 1967 - (DCSO records, Vol. 34 Page 14115)

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - M. Stone & V. Tracy, crew - Sept. 1963 - C.S. File 52/14-62

(Cont. Next Page)

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. cor. for 28, 29, 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Found - Brass cap set by cadastral survey in 1960.
7" W.Fir N.38°W., 29.7 ft. scribing visible in nearly healed scar.
9" D.Fir S.35°W., 67.3 ft. scar pitched over.
30" Madrone S.52°W., 51.5 ft. Blaze & rescribe this tree: "T22S R8W S32 CS BT."
24" Madrone S.61°E., 33.0 ft. Blaze & rescribe this tree: "T22S R8W S33 CS BT."
48" D.Fir (not called for in notes) N.68°E., 44.2 ft. mkd. T22S R8W S28 BT.

Fd. OK, May 1995 - M 122-62

BLM remonumentation by Aaron M Graham, Cadastral Surveyor & Michael O Jones Surveying Tech, under Group No 2241, surveyed Nov. 2008/April 2009 - (DCSO records Vol. 56 Page(s) 22112)

The cor. of secs. 28, 29, 32, and 33, remonumented by Brooks in 1960; monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd. from which the remains of the original bearing trees
A madrone, 33" dia., bears S.61°E., 33.0 ft., no marks visible.
A madrone, 39" dia., bears S.52°W., 51.5 ft., no marks visible.
and bearing trees mkd. by Brooks
A fir, 21" dia., bears S.35°W., 67.3 ft., with a healed blaze.
A dead fir snag, 11" dia., bears N.35°W., 29.7 ft., with a healed blaze. (Record, N.38°W.)
and a new bearing tree
A fir, 26" dia., bears N.40°W., 30.4 ft., mkd. T22S R8W S29 BT.