TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1574)

Set ¼ sec. post, from which
A W.Oak 10" dia., bears S.35°E., 232 lks. dist.
A W.Oak 18" dia., bears N.71½°W., 558 lks. dist.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13695)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼
S 17 S 16
T 22 S R 8 W
1963

from which
An Oak 42" dia., bears S.69°E., 44 lks. dist. mkd. ¼ S16 BT.
A Fir 8" dia., bears S.78°W., 15 lks. dist. mkd. ¼ S17 BT.

Carl Sweeden - For: Louis Van't Zet - January 2001 - M 136-34

Found - BC & pipe laying over in grove of reprod, repositioned BC to vertical & set in using BTs to adjust.
37" Oak stump S.69°E., 29.04', bark gone, portion of scribe visible stump is forked & approx. 7' tall.
12" D.Fir stump S.78°W., 9.9', badly rotted, portion of reverse scribe visible on the inside after removal of interior rotted. wood.

New BTs- 12" D.Fir BT N.47°E., 6.10', tag, BT mkd: "W¼ S16 BT T22S R8W"
10" D.Fir BT N.33°W., 11.0', tag, BT mkd: "E¼ S17 BT T22S R8W"
11" D.Fir BT S.68°W., 14.7', tag, BT mkd: "E¼ S17 BT T22S R8W"
10" D.Fir BT S.31°E., 38.9', tag, BT mkd: "W¼ S16 BT T22S R8W"