

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 202 survey dated March 11, 1874 (DCSO records Vol. 4 Page(s) 1592)

Marked a Fir 24" dia., for 1/4 sec. cor.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13697)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

1/4
S 8 | S 9
T 22 S R 8 W
1963

from which

A Fir 10" dia., bears N.83°E., 164 lks. mkd. 1/4 S9 BT

A W.Fir 10" dia., bears S.51 1/4°W., 91 lks. mkd. 1/4 S8 BT.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2180 & 2300, surveyed May/Oct. 2007 (DCSO records Vol. 56 Page(s) 22218)

The 1/4 sec. cor. of secs. 8 & 9, reestablished by Brooks & Jelley in 1963-65; monumented with an iron post, 2 1/2" dia., firmly set, projecting 11" above ground, with brass cap (properly) mkd.

from which the remains of the BTs mkd. by Brooks and Jelley
A fir, 34" dia., bears N.82 1/4°E., 108.2 ft., with a healed blaze. (Record, N.83°E.)

A decayed W.Fir stump, size indeterminate, bears S.51 1/4°W., 60.1 ft., no marks visible.

and a new bearing tree

A fir, 9" dia., bears S.44 3/4°W., 60.2 ft., mkd. 1/4 SEC9 BT.

A BLM location tag dated 1973 is on a hemlock, 4 ft. dia., E., 15 ft., from the cor.

Corner is located on a gentle S. slope, and S., 1100 ft. from a ridge, extending N.35°E. and S.60°W.