

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 303100

PRIMARY CORNER DESCRIPTION C C for secs. 4 & 5 only, T23-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2596-97)

Intersect N. bdy. of T23S R8W, 2.98 chs. E. of cor. to secs. 32 and 33. At which point I set a post 4 ft. long 4" sq. 24" in the ground for closing cor. to secs. 4 and 5, mkd. CC T23S R8W on S.; S4 on E.; and S5 on W. with 4 notches on E. and 2 notches on W. sides, from which

A Fir 24" dia., bears S.1°E., 7 lks. mkd. T23S R8W S4 BT.
A W.Fir 10" dia., bears S.26°W., 28 lks mkd T23S R8W S5 BT
A Fir 24" dia., bears N.28°W., 15 lks. mkd. T23S R8W CC S4 & 5 BT.

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #436, Surveyed May/June 1962 (DCSO records Vol. 31 Page(s) 13105)

Point for the closing cor. of secs. 4 & 5, T23S R8W, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22 S
S 33
S 5 | S 4
C C
T 23 S R 8 W
1962

from which

A Fir 8" dia., bears S.20°E., 94 lks mkd T23S R8W S4 CC BT
A W.Fir 11" dia., bears S.62°W., 55 lks. mkd. T23S R8W S5 CC BT.

BLM resurvey by Michael O. Jones, Cadastral Surveyor under special instructions dated May 27, 2009 - Surveyed June/July 2009 - (DCSO records BLM plat 2011 & Vol. 56 Page 22267)

The closing cor. of secs. 4 & 5 on the N. bdy. of the Tp., (Fifth Standard Parallel South), reestablished by Brooks in 1962; monumented with an iron post, 2 1/2" dia. firmly set, projecting 5" above the ground, with a brass cap (properly) mkd., from which new bearing trees

A fir, 11" dia., bears S.50°E., 18.4 ft., mkd. T23S R8W S4 CC BT.
A fir, 8" dia., bears S.43°W., 10.3 ft., mkd. X BT.