

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 32 & 33 only, T21-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 376 survey dated Jan. 22, 1881 (DCSO records Vol. 2 Page(s) 837)

Set Maple post for sec. cor. to secs. 33 and 32, from which
 An Alder tree 8" dia., bears N.52°E., 42 lks.
 An Alder tree 8" dia., bears N.58°W., 69 lks.

Cor. Fd. and used in GLO survey by Wm. Wright, under Contract #486, dated Aug. 1, 1883 (DCSO records, Vol. 2 Page 865)

GLO resurvey by Norman D. Price, Cadastral Engineer and Geo Rigby, Assoc. Cadastral Engineer, under Group #282, surveyed May/Aug. 1945 (DCSO records Vol. 27 Page(s) 11377)

The corner of sections 32 and 33, the locus of which is determined at the record bearing and distance from the old NE bearing tree.

At point for corner,
Set an iron post 3 ft. long, 2" dia., 28" in the grund, for cor., with brass cap mkd. T 21 S R 8 W

	<u>S 32</u>	<u>S 33</u>	
	T 22	S R 8 W	
	S 4		
	1945		

from which

- An Alder 18" dia., bears N.52°E., 42 lks. dist. with no marks remaining on decayed face of old blaze. (Old BT)
- A Fir 36" dia., bears N.45½°E., 52 lks. dist. mkd. T21S R8W S33 BT. (New BT)
- A Cedar 6" dia., bears N.70°W., 53 lks. dist. mkd. T21S R8W S32 BT.

This sec. cor. is located in head of ravine, course S., at upper edge of an old landslide.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13677)

The cor. of secs. 32 and 33, monumented with an iron post, 2" dia., 10" above ground, firmly set, with brass cap, properly mkd.

from which the bearing trees mkd. by Price:

- A down Fir 38" dia., bears N.45½°E., 53 lks. dist. with a healed blaze.
- A Cedar 14" dia., bears N.70°W., 55 lks. dist. with a healed blaze. (Rec. dist., 53 lks.)

(Cont. Next Page)

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

<p>and a new bearing tree, A Fir 23" dia., bears N.47°E., 66 lks. dist. mkd. T21S R8W S33 BT.</p>
<p>Douglas County Surveyors Office - Randall Smith & Stephen Flause - Mar. 13, 1997 - C.S. 64/71-20 -----</p> <p>Fd - 2½" dia. Brass cap on a 2" O.D. Iron pipe, protrudes 12" above ground. (1945). No OBT's Found 36" dia. now 38" dia. down D.Fir, bears N.45½°E., 35' (agrees with 1965 renewal). 6" now 18" dia. 2½' High Cedar stump with a healed blaze, bears N.70°W., 36.3' (agrees with 1965 renewal). 23" now 30" dia. D.Fir with a fully healed single blaze, bears N.53°E., 43.6' (rec. N.47°E., 43.6' possible compass reading error) 1965.</p> <p>New BTs- 20" dia. W.Fir double blazed and scribed "T21S R8W S32 CS BT", bears N.47°W., 14.6'. 10" dia. Maple double blazed and scribed "T21S R8W S33 CS BT", bears N.60°E., 20.2'. 16" dia. W.Fir double blazed and scribed "T21S R8W S33 CS BT", bears N.80°E., 69.3'. Corner lies on a steep southerly slope in a slide area.</p>
<p>Gary Smithers - Feb. 2004 - C.S. File 65/49-23 -----</p> <p>Found - 1945 Brass Cap on Iron Pipe firmly set. We set a 6 ft. galvanized steel fence post alongside with top painted red.</p> <p>Old Bearing Trees Taken in 1945 to Witness Corner by GLO: 38" D.Fir is down, N.45½°E., 35 ft with healed face. 18" rotted Cedar Stump, N.70°W., 36.3 ft no marks, no tag. 31" D.Fir Snag, N.53°E., 43.6 ft with healed face and tag.</p> <p>Bearing Trees taken in 1997 by Douglas County Surveyor: 22" W.Fir, N.47°W., 14.6 ft with visible scribe and aluminum tag. 11" Maple, N.60°E., 20.2 ft with healed face and aluminum tag. 17" W.Fir, N.80°E., 69.3 ft with healed face and aluminum tag.</p>