

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Section 33

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13729)

Point for the center ¼ sec. cor. of sec. 33, at intersection with the E. and W. center line.

Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked: C ¼ S 33

1964

from which

A Fir 4" dia., bears S.41°E., 50 lks. mkd. C¼ S33 BT

A Fir 5" dia., bears S.74½°W., 35 lks. mkd. C¼ S33 BT.

Ron Rice - Josh Reed - 7/8/2010 - C.S. File 65/69-40

Found - 3¼" BLM brass cap dated 1964 with the following accessories:

16" D.Fir bears S.74½°W., 23.1' healed face

15" D.Fir bears S.41°E., 33.0' - healed face

New - 16" D.Fir bears N.81°E., 12.8' blazed, scribed "C¼ S33 BT"

9" D.Fir bears N.88°W., 11.9' - blazed, scribed "C¼ S33 BT"

Note - Corner has steel post adjacent to it. All BTs have red painted bands & yellow tag.

BLM remonumentation by Aaron M Graham, Cadastral Surveyor & Michael O Jones Surveying Tech, under Group No 2241, surveyed Nov. 2008/April 2009 - (DCSO records Vol. 56 Page(s) 22124)

The center ¼ sec. cor. of sec. 33, established by Brooks and Jelley in 1963-65; monumented with an iron post, 2½" dia., firmly set, projecting 5" above ground, with a brass cap (properly) mkd.

from which the bearing trees mkd. by Brooks and Jelley

A fir, 15" dia., bears S.41°E., 33.0 ft., with a healed blaze.

A fir, 16" dia., bears S.74½°W., 23.1 ft.,

(no other information on the BLM resurvey)

The geographic position (NAD 1983 (CORS 96)) of the center ¼ section corner of section 33, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's OPUS, is as follows:

Latitude: 43°36'49.81"N Longitude: 123°39'16.27"W