

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 351600

PRIMARY CORNER DESCRIPTION M. C. So. bdy. Sec. 4 (WC)

Alias 877820 Description M. C. Right bank Umpqua River
Alias 050030 Description Pt. on W. bdy. DLC #50
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1575-76)

Set meander post on right bank of Umpqua, from which
A W.Oak 4" dia., bears N.48°E., 34 lks. dist.
An Ash 15" dia., bears S.4°W., 25 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - M. Stone & V. Tracy, crew - Dec. 20, 1962 - C.S. File 52/14-44

Found - W.Oak now 24", N.48°E., 22.4 ft., cut open, found axe marks at least 60 years old where tree was opened previously. Also found small portion of straight scribe marks on piece of old face.
The center of a clump of young Ash trees growing in a circle, bears S.4°W., 16.5 ft.

This location also fits tie from NW corner DLC #50. Corner location too close to river.

SET WIT. COR. 20 FT. EAST OF M.C.

Set Brass cap at cor. mkd: County Surveyors Office
T 22 S R 8 W
WC 1855 WC \S 4
 \S 9
20 ft. W. to M.C.
1962

New BTs -18" D.Fir, North, 11.0 ft. mkd. W.C. M.C. S4 CS BT
10" Ash S.47°W., 26.8 ft. mkd. W.C. MC S9 CS BT.

This is a renewal of Gordon and Gardner's Meander Corner, 1855 survey. Byar's section line (1881 survey) is approx. 200 ft. South.

FD. OK - Les Roberts - M 124-44 & CS 65/12-5 A&B - 2-10-97

Douglas County Surveyors Office - Randall Smith & Stephen Flause - Mar. 17, 1997 - C.S. 64/74-6

Found - BC/IP from 1962 DCSO renewal not found area now below high bank.

Bearings and distance taken from W.C. Position

4" now 27" dia. W.Oak, with a previously opened blaze facing southwest no scribing visible, bears N.12½°W., 15.4' (Note this agrees with a calculated position using original and 1962 bearing & distance). 1855 OBT

18" now 26" dia. D.Fir, with a fully healed double blaze, bears North 11' (agree with rec.) 1962

No other BTs Found

(Cont. Next Page)

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 351600

PRIMARY CORNER DESCRIPTION M. C. So. bdy. Sec. 4

Alias 877820 Description M. C. Right bank Umpqua River
Alias 050030 Description Pt. on W. bdy. DIC #50
Alias _____ Description _____
Alias _____ Description _____

Set- 5/8"x5' long iron rod with Alum. cap marked W.C.
M.C. is set at a position determined by BT's for
witness corner. Protrudes 6" above ground.
2 3/8" dia. Brass cap on a 1 3/8" O.D. by 32" long iron
pipe is set at a point east 20' from W.C.
protrudes 3" above ground.

DOUGLAS COUNTY SURVEYORS

B0 1

WEST 20 FT

TO WC MC

1997

OFFICE

New BT- 6" dia. Ash double blazed and scribed "WC MC S9 CS
BT", bears S.64 1/2°E., 15.3'.

Fd. BC "B01" - Not FD WC BC 3/2020 - N Hibbs - M176-72

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff
Lorsung- 9/23/2021 (Filed 11/23/2021) - C.S. File 67/51-16

Found - 2 3/8" (DCS0 1997) brass cap (properly mkd) on
1 3/8" O.D. iron pipe protrudes 4" above ground.
38" D.Fir North 11.0 ft. fully healed double blaze
will be cut down soon.

(BC/IP 1997 "B01" bears East 20.0 ft.)

(1997 BT 11" Ash bears S.64 1/2°E., 15.3')

New - 16" Maple N.81 1/2°E., 26.0 ft. from 5/8"x60" WC to MC
scribe WC MC S9 CS BT

Note - See sketch in file
Compass decl. 15°E.