

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 366600

PRIMARY CORNER DESCRIPTION Wit. Cor. to Secs. 4 & 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1576)

-----  
Set post on bluff, from which  
A W.Oak 24" dia., bears N.49°W., 64 lks. dist.  
A W.Oak 24" dia., bears S.26°W., 64 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Vernon "Ray" Tracy, crew - Dec. 1962 - C.S. File 52/14-45

-----  
Found - Old W.Oak now 28", S.26°W., 42.2 ft. (slope dist.) showed scars on bark, opened tree and found it hollow. Very old axe marks found. Also portions of both upper and lower faces, no scribing found. Rotten remains of big Oak stump N.49°W., 42.2 ft. Too far gone to find scars or scribing.

This location is due East and approx. 15 chs. dist. from Meander Cor. bet. Secs. 4 & 9, Right bank of Umpqua River.

Set Brass cap at cor. mkd: County Surveyors Office  
T 22 S R 8 W  
W. C. S 4  
S 9

1962

New BTs -10" D.Fir S.13°W., 12.8 ft. mkd. WC S9 CS BT.  
11" D.Fir N.13°E., 14.3 ft. mkd. WC S4 CS BT.

This witness corner was set by Gordon and Gardner, 1855 survey.

FD. OK - Les Roberts - M 124-44 & CS 65/12-5 A&B - 2-10-97