TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 33 and 34

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1565-66)

Set ¼ sec. post, from which
A W.Oak 12" dia., bears S.58°W., 37 lks. dist.
A W.Oak 12" dia., bears N.29°E., (?) lks. dist.

BLM resurvey by Floyd Brooks, Cadastral Surveyor - under Group #436 - surveyed May/June 1962 - (DCSO records Vol. 31 Page(s) 13107)

The ¼ sec. cor., determined at record bearing and distance from the only remaining original bearing tree:
A W.Oak 22" dia., bears S.58°W., 37 lks. dist. with old axe marks but no scribe marks visible on the decayed face of an opened blaze. Residents of this area state that scribe marks were visible on the blaze several years ago.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: ¼
S 33 S 34
T 22 S R 8 W
1962
from which new bearing trees
A Fir 8" dia., bears N.20°E., 22 lks. dist. mkd. ¼ S34 BT.
A Fir 18" dia., bears N.33°W., 69 lks. dist. mkd. ¼ S33 BT.

Fd. OK, Sept. 1992, by L. Dolan, M 115-68