

PRIMARY CORNER DESCRIPTION Witness point on bdy bet 27 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1567)

Set post on bluff, from which
A Fir 36" dia., bears S.54°W., 26 lks. dist.
A Fir 14" dia., bears S.77°E., 78 lks. dist.

GLO survey by W.H. Byars, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 4 Page(s) 1606)

Old post, from which
A Fir 36" dia., bears S.54°W., 26 lks. dist.
A Fir 14" dia., bears S.77°E., 78 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Clete Putnam, crew - June 8, 1961 - C.S. File 52/80-2

This wit. cor. was set on original survey in 1855 and lies on top of a ridge about 683 ft. South of ¼ sec. cor. of 27 & 28, according to Byar's survey of 1881.
Found - Rotted stump S.77°E., 51.5 ft. with very plain scribing "BT".
Fir tree, now 48", S.54°W., 17.2 ft., showing bark scribing, "S28 2S". This tree still in good condition.

Set Brass cap at cor. mkd: County Surveyors Office
T 22 S R 8 W
W. C. S28 | S27
1961

New BT - 8" D.Fir N.34°E., 12.3 ft. mkd. W.C. S27 CS BT.

BLM resurvey by Floyd Brooks, Cadastral Surveyor - under Group #436 - surveyed May/June 1962 - (DCSO records Vol. 31 Page(s) 13108)

The original witness point established by Gordon and Gardner in 1855, on the line bet. secs. 27 and 28, bears N.0°59'., 30.23 chs. dist. from sec. cor. of 27, 28, 33 and 34, perpetuated and recorded by the County in 1961, monumented with an iron post, 1½" dia., firmly set, projecting 18" above ground, with 1961 brass cap
from which the original bearing trees

A rotted Fir stump 26" dia., bears S.78 ¾°E., 78 lks. dist., with scribe marks BT visible on opened blaze. (Rec. brg. S.77°E.)

A Fir 53" dia., bears S.58½°W., 26 lks. dist. with scribe marks WC S27 CS BT visible on unhealed double blaze.

I ADD the marks BLM 1962 to the brass cap.

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 400231

PRIMARY CORNER DESCRIPTION Wit Point bet secs 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Fd. OK, by Brooks and Jelley in BLM resurvey, Group #'s 514 and 350 - surveyed June 1963/March 1965 (DCSO records Vol 33 Page 13688)

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Oct. 7, 1986 - C.S. File 62/37-1

Found - 1961 DCSO 2½" brass cap on a 1½" I.P. protruding 18" above ground, remarked 1962 by BLM.
Orig. 36" now 54" dia. D.Fir with bark scribing visible "28 S" and an H chopped in bark facing BC/IP, bears S.58½°W., 18.7 ft. to center. (Rec. orig. S.54°W.; BLM rec. S.58½°W., 17.2 ft. dist. is a face measurement)
SE BT is gone, a slight depression found at record bearing and distance.
8" Fir now a 12" dia. 1 ft. high D.Fir stump, bottom of blaze evident, no scribing found, bears N.34½°E., 12.2 ft. (agrees w/rec.)
New BTs -6" dia. D.Fir double blazed and scribed "WC S27 CS BT" bears S.17°E., 3.9 ft.
8" dia. D.Fir double blazed and scribed "WC S27 CS BT" bears N.10°E., 11.5 ft.
9" dia. D.Fir double blazed and scribed "WC S28 CS BT" bears N.31°W., 12.1 ft.
Corner lies on top, near East end of a E-W ridge.