

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1569)

Set post cor. secs. 21, 22, 27 and 28, from which
A Fir 36" dia., bears N.50°W., 123 lks. dist.
A Fir 8" dia., bears N.68°E., 24 lks. dist.
A Maple 4" dia., bears S.15°E., 24 lks. dist.
No tree visible in Sec. 28.

GLO survey by W.H. Byars, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 4 Page(s) 1606)

Set new post as per field notes furnished, viz.
A Fir 36" dia., bears N.50°W., 123 lks. dist.
A Fir 8" dia., bears N.68°E., 24 lks. dist.
A Maple 4" dia., bears S.15°E., 24 lks. dist.
Trees all standing.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13689-90)

The sec. cor., determined at record bearing and distance from the remaining original bearing tree,
A decayed Fir stump 12" dia., bears N.68°E., 24 lks. dist.
with fragmentary scribe marks visible on opened blaze.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 21" in the ground, with brass cap mkd:
T 22 S R 8 W
S 21 S 22
S 28 S 27
1963

from which new bearing trees
A Fir 8" dia., bears N.84°E., 106 lks. dist. mkd. T22S R8W S22 BT.
A Fir 12" dia., bears S.58½°E., 144 lks. dist. mkd. T22S R8W S27 BT.
A Fir 35" dia., bears S.24°W., 100 lks. dist. mkd. T22S R8W S28 BT.
A Fir 10" dia., bears N.22°W., 415 lks. dist. mkd. T22S R8W S21 BT.

Fd. OK, Jan. 1994, M 120-49 A&B.

continued next page

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Mark Smalley - For: Roseburg Resources - 12/2000 - M 132-59

Found - 1963 BLM brass cap on iron pipe in hole washed out
by creek.

21" Fir, N.84°E., 70.0 ft. healed.

24" Fir, S.58½°E., 95.0 ft. healed.

42" Fir, S.24°W., 66.0 ft. healed.

34" Fir, N.22°W., 273.9 ft. stump, 7 ft. tall.

Set - 5/8" x 48" iron rod & alum. cap 20.00 ft. north
marked "LS 2354 2000 WC 20' ↓"

24" W.Fir, N.60°E., 14.7 ft. "S22 WC BT"

24" Fir, N.7°W., 27.4 ft. "S23 WC BT"

10" Fir N.46°W., 58.2 ft. "S23 WC BT"

No other trees within reasonable distance.