

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 4 Page(s) 1603)

-----  
Set Fir post for the ¼ sec. cor., from which  
A Fir 8" dia., bears N.68°E., 166 lks. dist.  
A Fir 24" dia., bears N.62°W., 182 lks. dist.

Douglas County Surveyors Office - Milo E. Godfrey, Deputy - C.S. File 52/14-134 - Nov. 29, 1962

-----  
Corner searched for, not found. At approx. position for ¼ cor. for 3 & 4, found iron pipe 1" x 36", above ground. No BTs found.

Survey by Les Roberts, LS #1039 - For: International Paper Co. - June 1986 - M 102-18 & C.S. File 63/18-5(J)

-----  
Found - 48" Fir stump bears N.68°E., 109.5 ft., scribe visible. 1881 BT.  
68" Fir bears N.62°W., 141.2 ft. (Rec. N.62°W., 120.1 ft.) Scar visible. 1881 BT.

Set 1¼" x 36" Iron pipe and brass cap stamped "T22S R8W ¼ S4|S3 1986 PLS. 1039". Buried purple magnetic marker under IP Old 1" I.P. bears S.6°20'15"W., 77.81 ft.

New BTs -9" Fir bears S.76°W., 10.9 ft., scribed/painted red.  
12" Fir bears S.47°E., 23.2 ft. scribed/painted red.

Set metal fence post, with survey monument sign wired to, beside brass cap. Corner lies on West slope about 50 ft. West of 10 year old logged unit. Corner set by using record data from orig. NE BT, fits for bearing but not for distance as noted.

Les Roberts - Feb. 10, 1997 - M 124-44 & C.S. 65/12-5 A&B

-----  
Fd Ok - (except for a 1" Iron pipe, bears S.6°20'15"W., 77.81 - Origin unknown)

BLM dependent resurvey by Aaron M Graham, Cadastral Surveyor, under Group 1910, surveyed June/July 1999. (DCSO recs. Vol. 53 Page(s) 20495)

-----  
From the ¼ sec. cor. of secs. 3 & 4, perpetuated by Roberts, in 1986, utilized by Baker, in 1989, and further utilized by Roberts, in 1997; monumented with an iron post, 1½" diam., firmly set, projecting 6" above the ground, with brass cap mkd.

continued next page

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

T 22 S R 8 W  
                  <sup>¼</sup>  
                  S 4 | S 3  
                  1986  
                  LS 1039

from which the remains of an original bearing tree  
A fir stump, 47" diam., bears N.68°E., 109.6 ft., with illegible scribe marks visible on open blaze.  
and the remains of bearing trees mkd. by Roberts  
A fir, 14" diam., bears S.47½°E., 23.2 ft., with a healed double blaze.  
A fir snag, 11" diam., bears S.74°W., 10.9 ft., with a healed double blaze.  
and a new bearing tree  
A fir, 12" diam., bears S.26½°W., 25.0 ft., mkd. ¼ S4 BT.  
Each new bearing tree has a 2½ inch x ¼ inch magnetic nail (Mag Nail) driven at the base on right side-center, unless otherwise noted in the corner description.