

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4, T23-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - M. Stone & V. Tracy, crew - Sept. 1963 - C.S. File 52/14-64

Found - Old Fir stump S.52½°E., 179.5 ft., cut open and found it had been opened many years ago and grown over axe notch at bottom of badly burned old face. No scribing found.

Stump hole with Fir roots, S.31°W., 91.1 ft.

These two BTs were same trees used as BTs for standard corner secs. 3 & 4, which was 60 lks. East of this corner. This location is 10 ft. longer than record distance from C C secs. 33 and 34, T22-8 as set by Cadastral survey of 1963.

Set Brass cap at cor. mkd: County Surveyors Office 1963

S 4		S 3
C C		

T 23 S R 8 W

New BTs -31" B.Oak S.84°E., 137.5 ft. mkd. T23S R8W CC S3 CS BT.

17" W.Oak N.13°W., 23.8 ft. mkd. T23S R8W CC S3 S4 CS BT.

No trees near in section 4.

Corner lies 5 ft. South of E and W fence line.

Brass cap at C C sections 33 and 34 bears N.87°W., 221.7 ft.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #640, surveyed July 1967/April 1968 (DCSO records Vol. 35 Page(s) 14443-44)

(42.345 Chs.)

The original closing cor. of secs. 3 and 4, perpetuated and recorded by Godfrey in 1963, monumented with an iron post, 1½" dia., firmly set, projecting 10" above ground with brass cap, from which the original bearing trees

A sawed Fir stump 40" dia., bears S.52½°E., 272 lks. dist., with fragmentary scribe marks visible on opened blaze. (This tree was also used as the SE BT for the stan. cor. of secs. 3 and 4 established by Gordon and Gardner in 1855)

A Fir crown, size indeterminate bears S.31°W., 138 lks. dist. with no marks remaining. (This tree was also used as the SW BT for the stan. cor. of secs. 3 and 4 established by Gordon and Gardner in 1855)

and bearing trees mkd. by Godfrey

A W.Oak 32" dia., bears S.38½°E., 209 lks. dist. with scribe marks T23S R8W CC S3 CS BT visible on open double blaze.

(Cont. Next Page)

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 403100

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4, T23-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A W.Oak 18" dia., bears N.14°W., 36½ lks. dist. with scribe marks T23S 8 CC S3 CS BT visible on open double blaze.

(42.37 Chs.) (N.0°11"E.)

Intersect the S. bdy. of Sec. 34, T22S R8W and true point for the closing cor. of secs. 3 and 4.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22 S R 8 W
S 34
S 4 | S 3
C C
T 23 S R 8 W
1967

from which

A W.Oak 22" dia., bears S.55 3/4°W., 496 lks. dist. mkd. T23S R8W S4 CC BT.

No suitable tree available in sec. 3.

Page 14429

From this point the cor. of secs. 33 & 34 only T22-8 bears N.87°42'W., 2.76 chains.

Rob Ward, Ward North West Inc. - Witness: Ron Rice - 6/15/2000 - C.S. File 65/30-21

Found - 3¼" BLM Brass cap
39" W.Oak bears S.55 3/4°W., 327.4 ft., healed face.
Douglas Co. Brass cap bears South 1.9 ft.
30" W.Oak bears N.14°W., 24.1 ft. healed face.
New - 16" D.Fir bears S.21°W., 31.0 ft. blazed & scribed
T23S R8W S3 CC BT.
Note - All BTs have red painted bands and faces plus yellow
BT tags. Steel post set adjacent to corner.