

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 4 Page(s) 1607)

-----  
Set a Dogwood post for the ¼ sec. cor., from which  
A Fir 16" dia., bears S.60°W., 45 lks. dist.  
A Fir 60" dia., bears N.45°W., 8 lks. dist.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13690)

-----  
The ¼ sec. cor., determined at record bearing and distance from the original bearing trees:

A down Fir 48" dia., bears N.45°W., 8 lks. dist., with scribe marks ¼ S BT visible in bark.  
A down Fir 22" dia., bears S.60°W., 45 lks. dist. with no marks visible.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼  $\frac{S\ 22}{S\ 27}$   
T 22 S R 8 W  
1963

from which new bearing trees:

A Maple 10" dia., bears N.11½°E., 22 lks. dist. mkd. ¼ S22 BT.  
A Hemlock 13" dia., bears S.26½°W., 67 lks. dist. mkd. ¼ S27 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, and crew -Feb. 3, 1966 - C.S. File 52/14-144

-----  
Found - 1963 BLM brass cap, probably set from orig. BT., down.

8" Maple N.11½°E., 22 lks. (14.5 ft.) mkd. ¼ S22 BT  
12" Hemlock S.26½°W., 67 lks. (44.2 ft.) mkd. ¼ S27 BT.

Move Brass cap 100 ft. West and reset and ADD "W.C. 100 ft. E. to Cor." on brass cap.

Marked new BTs:

17" Hemlock N.40°W., 29.5 ft. mkd. WC ¼ S22 CS BT.  
17" Hemlock S.65°W., 5.7 ft. mkd. WC ¼ S27 CS BT.

This corner lies approx. 70 ft. West of proposed new road.

continued next page

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Mark Smalley - For: Roseburg Resources - 12/2000 - M 132-59

-----

Found - 1963 BLM witness corner brass cap on iron pipe.  
25" (17") Hemlock S.65°W., 5.7 ft. healed.  
24" (17") Hemlock N.40°W., 29.5 ft. healed.  
New BTs- 12" Hemlock N.15°W., 16.7 ft. "WC BT"  
7" Hemlock S.72°E., 15.3 ft. "WC BT"