

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1569)

Set ¼ sec. post, from which
A W.Oak 24" dia., bears S.20°W., 268 lks. dist.
A W.Oak 24" dia., bears N.11°E., 149 lks. dist.

GLO survey by W.H. Byars, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 4 Page(s) 1600)

Reestablished the same from notes furnished, viz.
A W.Oak 24" dia., bears N.11°E., 149 lks. dist.
A W.Oak 24" dia., bears S.20°W., 268 lks. dist.

Douglas County Surveyors Office - Milo E. Godfrey, Deputy - C.S. File 52/14-134 - Nov. 19, 1962

Corner searched for, not found.

Survey by Wilford N. Haines - For: George Vant Zet - Sept. 23, 1974 - M 54-32

No trace of original corner.
Set 5/8" Steel rod., from which
24" Fir S.43°E., 19.4 ft.
10" Fir N.52°E., 27.1 ft.

Fd. OK, April 1989 by D. Baker, M 101-55

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 7/21/2005 - C.S. File 67/10-39

Found - 5/8" iron rod, no cap, approx. 6" below ground.
Haines 1974
24" now 34" dia., D.Fir - healed blaze visible - bears S.43°E., 19.4 ft. 1974 BT (Agrees w/rec)
No trace of 1974 NE BT. Falls in logging Rd. (Rec. 10" Fir N.52°E., 27.1)
New - 15" dia., D.Fir double blazed & scribed "¼ S15 CS BT" bears S.89¼°E., 73.6 ft.
27" dia., D.Fir, double blazed & scribed "¼ S15 CS BT" bears S.22½°W., 24.8 ft.
23" dia., W.Oak, double blazed & scribed "¼ S10 CS BT" bears N.60¾°W., 115.7 ft.
Note - Corner lies on nearly flat land on South edge of logging Rd. Road bears N.80°E. - S.80°W.