

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 3 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 4 Page(s) 1602)

Set Fir post for ¼ sec. cor. from which
A Maple 10" dia., bears N.50°E., 38 lks. dist.
A Fir 10" dia., bears S.42°W., 11 lks. dist.

Douglas County Surveyors Office - Milo E. Godfrey, Deputy - C.S. File 52/14-134 - Nov. 29, 1962

Corner searched for, not found.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13692)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd:

¼ $\frac{S \ 3}{S \ 10}$
T 22 S R 8 W
1965

from which

A Fir 10" dia., bears N.43½°E., 78 lks. dist. mkd. ¼ S3 BT
A W.Fir 12" dia., bears S.73°E., 143 lks. mkd. ¼ S10 BT.

Fd. OK, May 1986 by L. Roberts, C.S. File 63/18-5(H)

Fd. OK by D. Edwards, Sept. 1999 - M133-39

BLM dependent resurvey by Aaron M Graham, Cadastral Surveyor, under Group 1910, surveyed June/July 1999. (DCSO recs. Vol. 53 Page(s) 20494-5)

The ¼ sec. cor. of secs. 3 & 10, utilized by Roberts, in 1986, and by Baker, in 1989; monumented with an iron post, 2½" diam., firmly set, projecting 5" above the ground, with brass cap mkd.

¼ $\frac{S \ 3}{S \ 10}$
T22S R8W
1965

from which bearing trees mkd. by Brooks and Jelley

A fir, 31" dia. bears N.43½°E. 51.5 ft. with healed blaze.
A W.Fir, 27" dia. bears S.73°E. 94.4 ft. with healed blaze
and a bearing tree mkd. by person(s) unknown
A maple, 23" diam., bears S.27 ¾°E., 56.8 ft., with a healed blaze.