

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION No. 1/4 Corner for Sec. 3 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by M. Lytle; P. Norseth; T. Tillman; R. Bicknell; J. Gawron & H. Thielsen, Cadastral Engineers, under Group #304, surveyed Aug. 1952-Oct. 1954 (DCSO records Vol. 30 Page(s) 12548)

-----  
Point for the  $\frac{1}{4}$  sec. cor. of sec. 3, at proportionate distance.

Set an iron post 3 ft. long, 1" dia., 27" in the ground, with brass cap marked:

$\frac{1}{4}$  S 3  
1952

from which

A Fir 45" dia., bears S.63°E., 52 lks. dist. mkd.  $\frac{1}{4}$  S3 BT.

A Fir 35" dia., bears S.7°45'W., 124 lks. dist. mkd.  $\frac{1}{4}$  S3 BT.

Fd. OK, May 1986, Les Roberts, C.S. File 63/18-5(I)  
Fd. OK, May 1989, D. Baker, M 101-54

Greg Lang - Jan. 2005- C.S. File 65/54-3

-----  
Found - Brass Cap and Bearing Trees set in 1952;  
A 43 $\frac{1}{2}$ " Fir bears S.62°E., 33.73' (S.63°E. 34.32')  
A 42" Fir bears S.8 $\frac{1}{2}$ °W., 81.67' (S.7°45'W., 81.84')  
New - A 11" D. Fir bears N.45 $\frac{1}{2}$ °W., 10.30' scribed "BT"  
A 16" D. Fir bears N.17 $\frac{1}{2}$ °E., 16.40' scribed "BT"  
Note - Corner is located on a steep southwest slope, 160' easterly of a tributary to Cedar creek.