

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 452700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 34 only, T21-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>New BT - 12" Hemlock S.17°E., 15.2 ft. (from brass cap) mkd. ¼ S34 CS BT. No lives trees available North of line. Corner lies on top of ridge, just South of South edge of logging road.</p>
<p>Survey by Les Roberts - For: International Paper Co. - June 1986 - M 102-18 C.S. File 63/18-5(K) ----- Found - 1952 GLO brass cap set firmly in ground mkd. W.C. 30" Corner tree bears West, 1.98 ft. 24" Fir stump bears N.54°E., 25.2 ft., scribe visible. 1952 BT. Rec. N.54½°E., 25.7 ft. New BT - 8" Fir bears N.17°W., 12.6 ft., scribed/painted red. Set metal fence post with survey attention sign wired to, beside brass cap. Corner lies on South slope about 50 ft. South of old dirt logging road.</p>
<p>Greg Lang - Jan. 2005- C.S. File 65/54-2 ----- Found - Brass Cap Witness corner and it's Bearing Trees; A 28" Fir stump bears N.54°E., 25.13' (N.54½°E 25.74' per 1952 resurvey) (N.54°E., 25.2' per 1963 renewal) A 10½" D. Fir bears N.18¼°W., 12.80' (N.17°W., 12.6' per 1986 renewal) The true corner which is a 35" D.Fir bears N89°29'W 2.88 feet (N89°29'W 1.98' per 1952 resurvey) New - A 14½" D.Fir bears N.66½°E., 19.70' from the brass cap witness corner and is marked "X" "BT" A 8" D.Fir bears S.11½°E., 16.90' from the brass cap witness corner and is marked "X" "BT" A 17½" D.Fir bears S.42½°W., 56.80' from the brass cap witness corner and is marked "X" "BT" Note - Corner is located on a south slope, 300' southeasterly of a rock road.</p>
<p style="text-align: right;">2</p>