

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 34 and 35 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1560)

Set post cor. to secs. 34 and 35, from which
A Maple 10" dia., bears N.33°W., 48 lks. dist.
A Fir 24" dia., bears N.53°E., 128 lks. dist.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #640, surveyed July 1967/April 1968 (DCSO records Vol. 35 Page(s) 14427)

The cor. of secs. 34 and 35 only, determined at record bearing and distance from the original bearing trees
A Fir 65" dia., bears N.53°E., 128 lks. with healed blaze.
A Maple 25" dia., bears N.33°W., 48 lks. with no marks remaining on rotted blaze.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22 S R 8 W
S 34 | S 35

T 23 S R 8 W
S 3
1968

from which
A Fir 16" dia., bears N.34°W., 179 lks mkd T22S R8W S34 BT
Corner is located at top of ascent, slopes N.

BLM Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2772, surveyed Sept./Nov. 2014 - (DCSO records Vol. 58 Page(s) 23269-70)

The cor. of secs. 34 & 35 only, on the S. bdy. of T22S R8W monumented with an iron post, 2½" dia., firmly set, projecting 2" above ground, with a brass cap (properly) mkd. from which the original bearing trees

A fir, 58" dia., bears N.53°E., 84.5 ft., with a healed blaze.

A maple, 24" dia., bears N.29°W., 31.7 ft., with a decayed, hollowed-out blaze. (Record, N.33°W.)
and a bearing tree mkd. by Peterson in 1967-68

A fir, 31" dia., bears N.33°W., 118.1 ft., with a healed blaze. (Record, N.34°W.)

From this cor., a point established by person(s) unknown bears S.48°38'24"W., 0.88 ft., monumented with an iron pipe, 1" dia., firmly set, projecting 9" above ground.

continued next page

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 34 and 35 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From this same cor., a point established as the E 1/16 sec. cor. of sec. 34, on the S. bdy. of T22S R8W by Dolan, in 1992, bears N.89°38'49"W., 1319.01 ft., and is not utilized in this survey; monumented with an iron rod, 5/8" dia., firmly set, projecting 3" above ground, with a yellow plastic cap mkd. LS 1076. A steel fence post is alongside the monument.

Note: On Dolan's plat of survey the E 1/16 sec. cor. of sec. 34 is established at midpoint between the cor. of secs. 34 and 35 and the calculated position for the 1/4 sec. cor. of sec. 34, on the S. bdy. of T22S R8W. The calculated position he utilized for the 1/4 sec. cor. of sec. 34 was at proportionate measurement between the 1/4 sec. cor. of sec. 3 and the W 1/16 sec. cor. of sec. 3, on the N. bdy. of T23S R8W, established by Peterson in 1967-68. This position places the 1/4 sec. cor. of sec. 34 at approximately record from the standard cor. of secs. 34 and 35 instead of at proportionate between the cor. of secs. 34 and 35 and the angle point on the N. bdy. of sec. 3, of T23S R8W.

Fd as per rec. 3/2021 by D.Edwards - M179-24A&B