

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1560)

Set post cor. to secs. 26, 27, 34 and 35, from which
A B.Oak 15" dia., bears N.42°W., 40 lks. dist.
A B.Oak 10" dia., bears N.85°E., 49 lks. dist.
A B.Oak 24" dia., bears S.15°W., 81 lks. dist.
A Fir 30" dia., bears S.33°W., 96 lks. dist.

BLM resurvey by Floyd Brooks, Cadastral Surveyor - under Group #436 - surveyed May/June 1962 - (DCSO records Vol. 31 Page(s) 13109)

The sec. cor., determined at record distance from the original bearing trees:

- A decayed B.Oak stump 17" dia., bears N.88°E., 49 lks. dist. with no marks remaining on the rotted face of blaze. (Rec. brg. N.85°E.)
- A Fir 65" dia., bears S.33°E., 96 lks. dist. with a healed blaze.
- A B.Oak 33" dia., bears S.16½°W., 68 lks. dist. (dist. on slope, 81 lks.) with no marks remaining on the opened and decayed blaze. (Rec. brg. & dist. S.15°W., 81 lks.)
- A B.Oak 18" dia., bears N.47°W., 40 lks. dist. with no marks remaining on the opened and decayed blaze. (Rec. brg. N.42°W.)

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22 S R 8 W
S 27 | S 26
S 34 | S 35
1962

from which new bearing trees

- A Fir 6" dia., bears N.69°E., 86 lks. dist. mkd. T22S R8W S26 BT.
- A Dogwood 6" dia., bears S.38°W., 52 lks. dist. mkd. T22S R8W S34 BT.
- A Fir 4" dia., bears N.15°W., 22 lks. dist. mkd. T22S R8W S27 BT.

Fd. and used in BLM resurvey by Brooks & Jelley, under Contract #'s 514 & 350, surveyed June 1963/March 1965 (DCSO records, Vol. 33 Page 13685)

Survey by Donald L. Branch, L.S. #1137 - For: International Paper Co. - Jan/Feb. 1986 - M 100-31

Found - 1962 BLM brass cap on a 2" iron pipe.
No standing BTs found. (Cont. Next Page)

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec. cor. for 26, 27, 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs -6" D.Fir bears N.40°53'W., 14.45 ft. dist. scribed
T22S R8W S27 BT.
4" D.Fir bears N.67°30'E., 22.83 ft. scribed X BT.
5" D.Fir bears S.71°20'E., 34.35 ft. scribed X BT.
4" D.Fir bears S.64°24'W., 26.69 ft. scribed X BT.

Fd. OK, Sept. 1992 by R. Dolan, M 115-68

David Edwards - For: Beckley Brothers Millman Trust and
Roseburg Resources Co. - 1/2014 - M167-12

Found - BLM brass cap
A 10" dia. D.Fir bears N.67°30'E., 22.83 ft.
A 14" dia. D.Fir bears S.71°20'E., 34.35 ft.
An 11" dia. D.Fir bears S.64°24'W., 26.29 ft.
A 17" dia. D.Fir bears N.40°53'W., 14.45 ft.
All with healed blaze
Set - 6 ft steel post 2' East.

Fd as per rec by D. Edwards - 3/2021 - M179-24B