

PRIMARY CORNER DESCRIPTION Sec. cor. for 22, 23, 26 and 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1562)

-----  
Set post cor. to secs. 22, 23, 26 and 27, from which  
A Hemlock 20" dia., bears S.47°E., 19 lks. dist.  
A Hemlock 6" dia., bears S.75°W., 15 lks. dist.  
A Fir 5" dia., bears N.55°W., 31 lks. dist.  
A Fir 15" dia., bears N.57°E., 55 lks. dist.

GLO survey by W.H. Byars, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 4 Page(s) 1607)

-----  
Witness trees all standing. Set new post as per instructions, from which old witness trees:  
A Hemlock 20" dia., bears s.47°E., 19 lks. dist.  
A Hemlock 6" dia., bears S.75°W., 15 lks. dist.  
A Fir 5" dia., bears N.55°W., 31 lks. dist.  
A Fir 15" dia., bears N.57°E., 55 lks. dist.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13686)

-----  
Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner. (The departure of the east half mile between secs. 22 and 27 is based on the random line reported by Byars.)

Set an iron post, 28" long, 2½" dia., 24" in the ground with brass cap mkd:

T 22 S R 8 W  
S 22 S 23  
S 27 S 26  
1963

from which

- A Fir 9" dia., bears N.60½°E., 33 lks. dist. mkd. T22S R8W S23 BT.
- A Fir 8" dia., bears S.78°E., 26 lks. dist. mkd. T22S R8W S26 BT.
- A Fir 8" dia., bears S.74°W., 12½ lks. dist. mkd. T22S R8W S27 BT.
- A Fir 6" dia., bears N.48°W., 21 lks. dist. mkd. T22S R8W S22 BT.

Fd ok by Donald Branch 1/1986 - M 100-31

(Cont. next page)

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Corner Secs. 22, 23, 26, & 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Mark Smalley - For: Roseburg Resources - 6/30/1998 - C.S.  
File 65/20-41

-----  
Found - 1963 BLM Cad IPBC  
11" D.Fir, 8.3', S.74°W. - Good, healed face.  
8" D.Fir, 13.5', N.48°W. - Dead, healed face.  
13" D.Fir, 21.9', N.60°E. - Good, healed face.  
10" D.Fir, 17.0', S.78°E. - Good, healed face.  
New BT - 16" Fir, N.20°W., 14.2', scribed: "S22 BT"

Mark Smalley - For: Roseburg Resources - 12/2000 - M 132-59

-----  
Found - 1963 BLM brass cap on iron pipe.  
13" Fir, N.60½°E., 21.9 ft. healed.  
10" Fir, S.78°E., 17.0 ft. healed.  
12" Fir, S.74°W., 8.3 ft. healed.  
8" Fir, N.48°W., 13.5 ft. snag.  
New BT - 16" Fir, N.20°W., 14.2 ft. "S 22 BT"