

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 4 Page(s) 1600)

Set Maple post for the ¼ sec. cor., from which
A Fir 30" dia., bears S.18°E., 32 lks. dist.
A W.Fir 30" dia., bears S.25°W., 67 lks. dist.

Douglas County Surveyors Office - Milo E. Godfrey, Deputy - C.S. File 52/14-134 - Oct. 2, 1962

Corner searched for, not found. Fd. stake and yellow tag mkd. "approx. ¼ cor."

Survey by Les Roberts, L.S. #1039 - For: International Paper Co. - June 1986 - M 102-18 C.S. File 63/18-5(L)

Set 1¼" x 36" Iron pipe and brass cap stamped "T22S R8W 1/4 3|2 1986 P.L.S. 1039". Purple magnetic marker buried under 36" pipe.
BTs - 10" Fir bears S.13°W., 19.7 ft. scribed/painted red.
30" Fir bears N.6°W., 22.2 ft. scribed/painted red.
Set metal fence post, with land survey monument sign wired to, beside brass cap.
Corner lies on steep East slope about 150 ft. West of Paradise Creek Road.

Fd. & used on BLM dependent resurvey by Aaron M Graham, Cadastral Surveyor, under Group 1910, surveyed June/July 1999. (DCSO recs. Vol. 53 Page) (s) 20491-2)