

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 503100

PRIMARY CORNER DESCRIPTION Standard Cor. secs. 2 & 3 only, T23-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2772, surveyed Sept./Nov. 2014 - (DCSO records Vol. 58 Page(s) 23269)

The standard cor. of secs. 2 and 3 only, monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground, with a brass cap (properly) mkd.

from which the bearing trees mkd. by Whipple in 1894

A fir, 52" dia., bears S.25°E., 38.9 ft., with a healed blaze and axe marks B and T on either side of a tag. (Record, S.32½°E.)

A maple, 23" dia., bears S.7°W., 34.3 ft., no marks visible. (Record, S.3°W.)

A fir, 55" dia., bears N.80°W., 42.9 ft., with a healed blaze.

The geographic position in NAD 1983 (2011) of the following corners as determined by ties from temporary GPS control points, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's OPUS:

The standard corner of sections 2 and 3 only, on the north boundary of the township (Fifth Standard Parallel South):

Latitude: 43°36'22.98"N Longitude: 123°37'26.06"W