

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 26 and 35

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1561)

Set 1/4 sec. post, from which
A W.Oak 3" dia., bears N.50°E., 85 lks. dist.
A W.Oak 18" dia., bears S.71°E., 485 lks. dist.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13685)

Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner. No permanent monument established.

Survey by Donald L. Branch - For: International paper Co. - Jan/Feb. 1986 - M 100-31

Set a 2 1/2" x 30" Alum. pipe with cap mkd: LS 1137.
BTs - 8" Oak bears S.21°45'E., 73.61 ft. scribed 1/4 S35 BT.
8" Oak bears N.14°20'E., 129.63 ft. scribed 1/4 S26 BT.

David Edwards - For: Beckley Brothers Millman Trust and Roseburg Resources Co. - 1/2014 - M167-12

(Condition report)
Found - Alum. cap.
A 33" dia., Oak bears N.14°20'E., 128.5 ft.
A 26" dia., Oak bears S.21°45'E., 73.4 ft.
Both with healed blaze.