

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1562)

Set $\frac{1}{4}$ sec. post, from which
A Fir 36" dia., bears N.5°W., 50 lks. dist.
A Fir 20" dia., bears S.52°W., 67 lks. dist.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13687)

Point for the $\frac{1}{4}$ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
 $\frac{1}{4}$ $\frac{S\ 23}{S\ 26}$
T 22 S R 8 W
1964

from which
A Fir 4" dia., bears N.70°E., 30 lks. dist. mkd. $\frac{1}{4}$ S23 BT
A Fir 16" dia., bears S.9°E., 100 lks. dist. mkd. $\frac{1}{4}$ S26 BT

Survey by Donald Branch, L.S. #1137 - For: International Paper Co. - Jan/Feb. 1986 - M 100-31

Found - 1964 BLM brass cap on a 2" iron pipe.
25" D.Fir bears S.8°40'E., 66.11 ft. dist.
12" dead Fir bears N.70°07'E., 20.13 ft. dist.
New BT - 11" D.Fir bears N.17°27'W., 30.35 ft. dist. scribed $\frac{1}{4}$ S 23 BT.