

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 4 Page(s) 1599)  
-----

Set Fir post for ¼ sec. cor. from which  
 A Fir 60" dia., bears North, 20 lks. dist.  
 A Fir 50" dia., bears South, 5 lks. dist.

---

Wilford N. Haines - Haines field book H-103 (date unknown)  
-----

At the ¼ cor. for 2 and 11, find the BT in Sect 2 down. It has fell up the hill and slid down about 10 ft. There is scribe on the upper side. The ¼S is partly obliterated but the BT is plain. The tree in Sect 11 is down and mostly burned, there is no scribe.  
 (Note-I have made the assumption that this report is prior to the following Brooks and Peterson BLM resurvey. V. Laugen, June 1995)

---

BLM resurvey by Floyd Brooks and Peter Peterson, Cadastral Surveyors - under Group #'s 595 and 657 - surveyed Aug. 1965/Dec. 1967 - (DCSO records Vol. 34 Page(s) 14114)  
-----

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
 Set an iron post, 28" long, 2 1/2" dia., 25" in the ground, with brass cap mkd:  
                                   ¼  $\frac{S\ 2}{S\ 11}$   
                                   T 22 S R 8 W  
                                   1967

from which  
 A Fir 25" dia., bears N.45°E., 13 lks. dist. mkd. ¼ S2 BT  
 A W.Fir 6" dia., bears S.17°W., 18 lks. mkd. ¼ S11 BT.  
 Corner falls in ravine, drains S.15°E.

---

BLM Corrective Dependent Resurvey by John A. Farmer, March-April 1993 - D.C.S.O. Records Vol. 51, Pgs. 19549-19550.  
-----

Found - The 1/4 Sec. cor. of Secs. 2 & 11, perpetuated by Wilford N. Haines, Registered Land Surveyor No. 239, in 1950, from original evidence no longer in existence as reported in field tablet H-103 in the Douglas County Courthouse; monumented with an iron post, 1" dia., firmly set, projecting 24" above ground, from which the remains of bearing trees mkd. by Haines:  
 Found BTs -  
 A Fir, 22 ins. diam., bears S.76°W., 51 lks. dist., no visible marks.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 & 11

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A Fir snag, 32 ins. diam., bears N.61½°W., 134½ lks. dist., no visible marks.

A Fir, 44 ins. diam., with an old bearing tree tag attached and no visible marks, bears S.11°E., 67 lks. dist. (no record).

From this point, the 1/4 sec. cor. of secs. 2 and 11, **erroneously reestablished** by Brooks and Peterson in 1967, bears N.37°27'W., 0.994 chs. dist.; monumented with an iron post, 2½" diam., firmly set, projecting 4" above ground, mkd. and witnessed as described in the official record of the 1965-67 resurvey. Remove the iron post, obliterate the scribe marks on the SW. bearing tree, and at the corner point:  
Reset the iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T22S R8W

¼  $\frac{S\ 2}{S\ 11}$   
1993

From which a bearing tree mkd. by Brooks and Peterson

A Fir, 30 ins. diam., bears N.30¼°W., 101½ lks. dist., with healed blaze.

Deposit Haines' iron post at the base of the iron post.

Note - The corner is located on a small spur, slopes S.

BLM remonumentation by Aaron M Graham, Cadastral Surveyor and Michael Jones Surveying Technician under Group #2199 surveyed April 2008/April 2009 - (DCSO rec. Vol. 56 Pages 21941-2)

-----  
The ¼ sec cor of secs. 2 & 11, perpetuated by Haines in 1950, erroneously reestablished by Brooks and Peterson in 1965-67 and correctively resurveyed by Farmer in 1993; monumented with an iron post, 2½" dia., firmly set, with top flush with the surface of the ground, with a brass cap (properly) mkd. from which the remains of bearing trees mkd. by Haines in 1950 and reported by Farmer in 1993

A fir, 28" dia., bears S.76°W., 33.7 ft. no marks visible.

A fir stump, 32" dia., bears N.61½°W., 91.5 ft., with a healed blaze. (Record, 88.8 ft.)

and the remains of a bearing tree mkd. by Brooks and Peterson in 1965-67 and correctively resurveyed by Farmer in 1993

A decayed fir stump, 34" dia., bears N.30¼°W., 67.0 ft., no marks visible.

and a BT of unknown origin reported by Farmer in 1993

A fir, 50" dia., bears S.11°E., 44.2 ft. no marks visible.