

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 540700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 2 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by M. Lytle; P. Norseth; T. Tillman; R. Bicknell; J. Gawron & H. Thielsen, Cadastral Engineers, under Group #304, surveyed Aug. 1952-Oct. 1954 (DCSO records Vol. 30 Page(s) 12546)

-----  
Point for the ¼ sec. cor. of sec. 2 only, at proportionate distance.  
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, with brass cap marked:

¼ S 2  
1952

from which

- A Fir 48" dia., bears S.50½°E., 119 lks. dist. mkd. ¼ S2 BT.
- A Fir 70" dia., bears S.14½°W., 136 lks. dist. mkd. ¼ S2 BT.

M. Godfrey, DCSO, found the 70" Fir to be S.14½°E. C.S. File 52/14-31

Cor. Fd. OK, March 1983, Les Roberts, M 94-6