

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 35 only, T21-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 376 survey dated Jan. 22, 1881 (DCSO records Vol 2 Page 836)

-----  
Set Yew post for ¼ sec. corner from which:  
A Yew tree 10" dia., bears N.10°W., 20 lks.  
A Yew tree 6" dia., bears S.52°E., 27 lks.

GLO resurvey by M. Lytle; P. Norseth; T. Tillman; R. Bicknell; J. Gawron & H. Thielsen, Cadastral Engineers, under Group #304, surveyed Aug. 1952-Oct. 1954 (DCSO records Vol. 30 Page(s) 12545-46)

-----  
Point for the ¼ sec. cor. of sec. 35 only, determined from the original bearing trees:

A stump hole of a fallen Yew bears N.10°W., 20 lks. dist.  
A Yew 12" dia., bears S.52°E., 27 lks. dist. with scribe marks visible on opened blaze.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 24" in the ground, with brass cap mkd:  $\frac{1}{4} S 35$   
1952

from which

A hemlock 15" dia., bears N.57°45'E., 81 lks. dist. mkd.  $\frac{1}{4} S35 BT$ .  
A Fir 15" dia., bears N.1¼°W., 85 lks. dist. mkd.  $\frac{1}{4} S35 BT$

15" Hemlock found to be a sawed stump only on Set. 16, 1963 by M. Godfrey, DCSO. C.S. File 52/14-24,

Cor. Fd. OK, March 1983, Les Roberts, M 94-6

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2115, surveyed January/May 2007 (DCSO records Vol. 56 Page(s) 22052-3)

-----  
The ¼ sec. cor. of sec. 35 only, monumented with an iron post, 1" dia., firmly set, projecting 12" above ground, in rocky soil with a collar of stone, with brass cap mkd. from which the remains of the original bearing trees

A yew, 13" dia., bears S.52°E., 19.0 ft., with no scribe marks visible on partially healed blaze. (Rec, 17.8 ft)  
A roothole bears N.10°W., 13.2 ft., with a down yew, size indeterminate, alongside, no marks visible.

and the remains of the BTs mkd. by Lytle, et al., in 1952-54

A decayed hemlock stump size indeterminate bears N.57¾°E., 53.5 ft., no marks visible.

continued next page

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 549700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 35 only, T21-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 33" dia., bears N.1¼°W., 56.1 ft., with a healed blaze.

An iron rod with International Paper Co. property sign is alongside the cor.

The geographic position (NAD 1983 (CORS 96)) of the 1/4 section corner of section 35 only, on the south boundary of the township, as determined by a tie to the corner of sections 22, 23, 26, and 27, is as follows:

Latitude: 43°41'36.55"N.      Longitude: 123°36'46.88"W.