

TOWNSHIP 22 RANGE 08 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. cor. for 25, 26, 35 and 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1555)

-----  
Set post cor. of secs. 25, 26, 35 and 36, from which  
A W.Oak 20" dia., bears S.39°E., 609 lks. dist.  
A B.Oak 15" dia., bears S.12 3/4°W., 1148 lks. dist.  
A B.Oak 15" dia., bears N.83¼°E. (? lks.)  
No tree in sec. 26.

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records Vol. 33 Page(s) 13681)

-----  
Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22 S R 8 W  
S 26 S 25  
S 35 S 36  
1964

from which

A Fir 7" dia., bears N.79°E., 366 lks. dist. mkd. T22S R8W S25 BT.

A Fir 7" dia., bears S.53°E., 297 lks. dist. mkd. T22S R8W S36 BT.

A Fir 7" dia., bears S.57½°W., 399 lks. dist. mkd. T22S R8W S35 BT.

No suitable BT within limits in sec. 26.

Fd ok by Donald Branch 1/1986 - M 100-31